



TE Internal #: 3-1827159-8

PCB Mount Receptacle, Vertical, Board-to-Board, 8 Position, 1.25 mm [.049 in] Centerline, Tin (Sn), Surface Mount, Signal, Black, Tape & Reel

[View on TE.com >](#)

Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Receptacle**

PCB Mount Orientation: **Vertical**

Connector System: **Board-to-Board**

Number of Positions: **8**

Number of Rows: **1**

Features

Product Type Features

PCB Connector Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Board-to-Board Configuration	Parallel
Stackable	Yes
PCB Mount Orientation	Vertical
Number of Positions	8
Number of Rows	1

Electrical Characteristics

Operating Voltage	50 VAC
Insulation Resistance	1 MΩ



Dielectric Withstanding Voltage (Max)	500 VAC
---------------------------------------	---------

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Mating Pin Diameter	.5 mm[.019 in]
Contact Mating Area Plating Material Thickness	.8 µm[31.5 µin]
PCB Contact Termination Area Plating Material Thickness	.8 µm[31.5 µin]
Contact Layout	Inline
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Tin (Sn)
Contact Type	Socket
Contact Current Rating (Max)	.5 A

Termination Features

Rectangular Termination Post & Tail Width	1.8 mm[.07 in]
Rectangular Termination Post & Tail Thickness	.3 mm[.011 in]
Termination Method to PCB	Surface Mount

Mechanical Attachment

Mating Alignment Type	Polarization
PCB Mount Retention Type	None
PCB Mount Alignment Type	Locating Posts
PCB Mount Retention	Without
PCB Mount Alignment	With
Connector Mounting Type	Board Mount
Mating Alignment	With

Housing Features

Mating Entry Location	Top
Housing Material	Polyphenylene Sulfide (PPS)
Centerline (Pitch)	1.25 mm[.049 in]

Dimensions

Stack Height	5 mm, 6.5 mm, 7 mm, 10.5 mm[.197 in][.256 in][.276 in][.413 in]
--------------	---



Usage Conditions

Housing Temperature Rating	High
Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]

Operation/Application

Assembly Process Feature	Pick and Place Cover
Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	1000
Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Reflow solder capable to 245°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

TE Part # 6-720999-3
COVER TAPE 12W FOR 1.25 FP

TE Part # 1-720999-4
EMBOSS TAPE 16W-1580 HOLE

Customers Also Bought

TE Part #120953-3
UPM EXPANDED RCPT ASSEMBLY

TE Part #3-2176328-0
CRGP 1206 2K7 1%

TE Part #1658641-2
HDP-20,PLUG,SIZE 5, 50 POSN

TE Part #6469294-1
HM ZD 4 PAIR RECEPTACLE ASSEMBLY

TE Part #7-1879510-9
CRGH0805 1% 7K5 0.33W

TE Part #1487596-3
USB, A-B, 28/24, BLACK, 1.8M

TE Part #CAT-3984552-PHITPS
CT Post Header Assembly: Part. Shrouded

TE Part #8-1879497-1
CRGH1206 5% 2K2 0.5W

TE Part #3-1614884-3
CPF 0805 47R 0.1% 25PPM 1K RL

Documents

Product Drawings
1.25FP,R08,SL,B,C,TR

Japanese

CAD Files
3D PDF
3D

3-1827159-8

PCB Mount Receptacle, Vertical, Board-to-Board, 8 Position, 1.25 mm [.049 in]
Centerline, Tin (Sn), Surface Mount, Signal, Black, Tape & Reel



Customer View Model

[ENG_CVM_CVM_3-1827159-8_O.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_3-1827159-8_O.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_3-1827159-8_O.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[AMP 1.25mm F-P Connector \(Board To Board\)](#)

Japanese

Product Specification

Japanese