



## jalas® GRAN PREMIO 1948S METATARSAL

EN ISO 20345:2011 S3, SRC, HRO, M, CI, HI  ASTM F2413-18 M/I/C Mt PR  ASTM F3445-21

Learn more

## METATARSAL IMPACT PROTECTION BOOT

A durable boot for heavy industrial work with Kevlar stitching for extreme heat resistance and great comfort. Provides the highest protection for welding and heat. Integrated impact protection of the metatarsal part of the foot. Nitrile outsole for excellent grip and excellent shock absorption with PORON® XRD in the insole. Nail protection in plasma-treated composite and toecap in aluminium for low weight. Full grain leather for good fit. A boot with the highest level of protection and comfort.

### CHARACTERISTICS

- Excellent grip
- Extra comfortable
- Excellent shock absorption
- Good fit
- High level of protection

### FUNCTIONS

- ProNose toe reinforcement
- Wide fit
- KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit)
- Heat-resistant upper
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Padded boot shaft
- Pull loops
- Specially designed details
- Double shock absorption zones
- Adjustable ankle strap
- Water repellent
- Flame retardant



*All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.*

# jalas® GRAN PREMIO 1948S METATARSAL

## PREVENTS RISK OF
Toe injuries, nail penetration, metatarsal injuries

## PRIMARY ENVIRONMENTS OF USE
Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration, oily and greasy environments, dirty environments, harsh environments

## PRIMARY AREAS OF USE
Hot work, metalwork, sheet-metal work, welding

## PRIMARY INDUSTRIES OF USE
Metal fabrication

## SPECIFICATION
**TYPE** Safety footwear, Boots/Ankle boots
**CATEGORY** Cat. II
**NAIL PROTECTION MATERIAL** Plasma-treated composite (PTC) textile
**FITTING** Wide
**COLLECTION** Gran Premio
**UPPER MATERIAL** Full-grain leather
**PRONOSE MATERIAL** PU
**TOECAP MATERIAL** Aluminium
**LINING MATERIAL** Polyester, polyamide
**INSOLE** FX2 Supreme
**INNERSOLE MATERIAL** Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in Poron® XRD®
**MIDSOLE MATERIAL** PU midsole
**OUTSOLE MATERIAL** Nitrile rubber outsole
**FASTENING** Hook-and-loop
**COLOUR** Black, Yellow
**NET WEIGHT, (SIZE 42)** 1.32 kg

## COMPLIANCE
CE Cat. II
EAC TP TC 019:2011
Information/UIS
EN ISO 20345:2011 S3, SRC, HRO, M, CI, HI
ASTM F2413-18 M/I/C Mt PR
ASTM F3445-21
ÖNORM Z 1259
DGUV 112-191

## FEATURES
- Anti-static properties
- Ergothan Shock Absorption System
- Heat-resistant upper
- Aluminium toecap
- Oil-resistant outsole
- ProNose toe reinforcement
- Nail protection in plasma-treated composite (PTC) textile
- Wide fit
- Heat-resistant outsole
- Water repellent

| SIZE | | | | ARTICLE NUMBER | EAN |
|---|---|---|---|---|---|
| EU | UK | US M | US W | | |
| 36 | 3 | 4 | 5 | 1948S-36 | 6408487545320 |
| 37 | 4 | 5 | 6 | 1948S-37 | 6408487545375 |
| 38 | 5 | 5½ | 6½ | 1948S-38 | 6408487545429 |
| 39 | 6 | 6½ | 7½ | 1948S-39 | 6408487545474 |
| 40 | 6½ | 7½ | 8½ | 1948S-40 | 6408487545528 |
| 41 | 7 | 8 | 9 | 1948S-41 | 6408487545573 |
| 42 | 8 | 9 | 10 | 1948S-42 | 6408487545627 |
| 43 | 9 | 9½ | 11 | 1948S-43 | 6408487545672 |
| 44 | 10 | 10½ | 11½ | 1948S-44 | 6408487545726 |
| 45 | 10½ | 11 | 12½ | 1948S-45 | 6408487545771 |
| 46 | 11 | 12 | 13 | 1948S-46 | 6408487545825 |
| 47 | 12 | 13 | 14 | 1948S-47 | 6408487545870 |
| 48 | 13 | 13½ | 14½ | 1948S-48 | 6408487545924 |

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com



*All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.*