

## PCB terminal block - SPTAF 1/ 4-5,0-IL - 1862291

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB terminal block, nominal current: 16 A, nom. voltage: 320 V, pitch: 5 mm, number of positions: 4, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, color: green



The figure shows a 10-position version of the product

### Why buy this product

- ✓ Time saving push-in connection, tools not required
- ✓ Defined contact force ensures that contact remains stable over the long term
- ✓ Intuitive use through colour coded actuation lever
- ✓ Small component size for applications where space is at a premium
- ✓ Quick and convenient testing using integrated test option



### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 STK                                                                                                   |
| Minimum order quantity               | 75 STK                                                                                                  |
| GTIN                                 | <br>4 055626 137612 |
| GTIN                                 | 4055626137612                                                                                           |
| Weight per Piece (excluding packing) | 2.670 g                                                                                                 |
| Custom tariff number                 | 85369010                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Dimensions

|              |       |
|--------------|-------|
| Length [ l ] | 11 mm |
| Pitch        | 5 mm  |
| Dimension a  | 15 mm |

# PCB terminal block - SPTAF 1/ 4-5,0-IL - 1862291

## Technical data

### Dimensions

|                       |            |
|-----------------------|------------|
| Width [ w ]           | 20 mm      |
| Constructional height | 8 mm       |
| Height [ h ]          | 10.6 mm    |
| Solder pin [P]        | 2.6 mm     |
| Pin dimensions        | 0,75 x 0,3 |
| Pin spacing           | 5 mm       |
| Hole diameter         | 1.1 mm     |

### General

|                                        |                     |
|----------------------------------------|---------------------|
| Range of articles                      | SPTAF 1/...-IL      |
| Insulating material group              | I                   |
| Rated surge voltage (III/3)            | 4 kV                |
| Rated surge voltage (III/2)            | 4 kV                |
| Rated surge voltage (II/2)             | 4 kV                |
| Rated voltage (III/3)                  | 250 V               |
| Rated voltage (III/2)                  | 320 V               |
| Rated voltage (II/2)                   | 630 V               |
| Connection in acc. with standard       | EN-VDE              |
| Nominal current I <sub>N</sub>         | 16 A                |
| Nominal cross section                  | 1.5 mm <sup>2</sup> |
| Maximum load current                   | 16 A                |
| Insulating material                    | PA                  |
| Solder pin surface                     | Sn                  |
| Flammability rating according to UL 94 | V0                  |
| Stripping length                       | 8 mm                |
| Number of positions                    | 4                   |

### Connection data

|                                                                            |                      |
|----------------------------------------------------------------------------|----------------------|
| Conductor cross section solid min.                                         | 0.2 mm <sup>2</sup>  |
| Conductor cross section solid max.                                         | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible min.                                      | 0.2 mm <sup>2</sup>  |
| Conductor cross section flexible max.                                      | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 0.75 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 0.75 mm <sup>2</sup> |
| Conductor cross section AWG min.                                           | 24                   |
| Conductor cross section AWG max.                                           | 16                   |



## PCB terminal block - SPTAF 1/ 4-5,0-IL - 1862291

### Approvals

Ex Approvals

---

#### Approval details

|                                |                                                                                   |                                                                                                                                                       |                 |
|--------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| cULus Recognized               |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-20061129 |
|                                | B                                                                                 | D                                                                                                                                                     |                 |
| mm²/AWG/kcmil                  | 24-16                                                                             | 24-16                                                                                                                                                 |                 |
| Nominal current I <sub>N</sub> | 8 A                                                                               | 8 A                                                                                                                                                   |                 |
| Nominal voltage U <sub>N</sub> | 300 V                                                                             | 300 V                                                                                                                                                 |                 |

### Accessories

#### Accessories

##### Screwdriver tools

Screwdriver - SZF 0-0,4X2,5 - 1204504



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.4 x 2.5 x 75 mm, 2-component grip, with non-slip grip

---

Screwdriver - SZF 1-0,6X3,5 - 1204517



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip