

1322610

https://www.phoenixcontact.com/in/products/1322610

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



CHARX connect modular, Type 2, Cable set for infrastructure charging socket, 32 A , 250 V AC, Accessories, Single wires, length: 1.5 m, Plug-in mounting, with slip-on sleeve at one end, Only for connection to second-generation infrastructure charging sockets from Phoenix Contact, IEC 62196-2

Product description

Cables with slip-on sleeves on one end for connection to infrastructure charging sockets, for charging electric vehicles (EV) with alternating current (AC), for installation in charging stations for electromobility (EVSE)

Your advantages

- · Protected against overheating with precise temperature measurement
- · Flexible mounting and easy maintenance with plug-in cables
- · Available with your logo on request for consistent branding of your charging station
- · Waterproof and dirtproof due to fully molded contacts
- · Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001
- Uniform, space-saving installation space

Commercial data

Item number	1322610
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	XWB
Product key	XWBAFC
GTIN	4063151674496
Weight per piece (including packing)	308 g
Weight per piece (excluding packing)	308 g
Customs tariff number	85444290
Country of origin	DE



1322610

https://www.phoenixcontact.com/in/products/1322610

Technical data

Product properties

Product type	Cable set for infrastructure charging socket
Product family	CHARX connect modular
Application	Only for connection to second-generation infrastructure charging sockets from Phoenix Contact
Туре	Accessories
Design	with slip-on sleeve at one end
Charging standard	Type 2
Charging mode	Mode 3, Case B

Electrical properties

Note on the connection method	Plug-in connection, separable
Type of charging current	AC single-phase
Charging power rating	7.4 kW (32 A, 1-phase)
Charging power	8 kW (1-phase)
Charging current	32 A AC (1-phase)

Power contact

Number	3 (L1, N, PE)
Rated voltage	250 V AC
Rated current	32 A AC

Signal contact

Number	2 (CP, PP)
Rated voltage	30 V AC
Rated current	2 A

Material specifications

Material (Contact surface)	Silver
Cable/line	
Cable length	1.5 m
Cable type	Single wires
Cable structure	3 x 6.0 mm² + 2 x 0.5 mm²
Single-core wires for AC	
Cable length	1.5 m
Cable structure	3 x 6 mm²
Single-core wires for communication	
Cable length	1.5 m
Cable structure	2 x 0.5 mm ²



1322610

https://www.phoenixcontact.com/in/products/1322610

Mechanical properties

Mechanical data	
Insertion/withdrawal cycles	< 3
Environmental and real-life conditions	
Ambient conditions	
Ambient temperature (operation)	-30 °C 50 °C
Ambient temperature (storage/transport)	-40 °C 80 °C
Altitude	5000 m (above sea level)
Standards and regulations	
Standards	
Standards/regulations	IEC 62196-2
Mounting	
Mounting type Cable set	Plug-in mounting



1322610

https://www.phoenixcontact.com/in/products/1322610

Classifications

ECLASS

	ECLASS-11.0	27144792
	ECLASS-12.0	27144792
	ECLASS-13.0	27144792
ETIM		
	ETIM 9.0	EC002884
UNSPSC		
	UNSPSC 21.0	39121500



1322610

https://www.phoenixcontact.com/in/products/1322610

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in