

Datasheet

Product Name: UL1371 28AWG
Product Discription: UL1371 28AWG
Specification No.:
Customer's Name:

						Ouotomoi o itamo.			
Description					Construction				
Rated Vo	oltage:	Voltage	e not specified	t	Conductor	Stranded Sliver plated co	opper		
Rated Te	emperature: 105 c	deg C,60 or 80 o	deg C Oil, Gasoli	ne Resistant	Size(AWG)	28			
Reference	rence Standard: UL758		Construction(±0.008mm)	7/0.127					
Cross Section					Stranded Dia.(mm)Ref.	0.38			
					Insulation Material PTFE				
					Insulation Color	ANY COLOR			
					Ave Thickness(mm)	0.15			
					Insulation Dia.(±0.05mm)	0.74			
Marking					Remark:				
					9033964 Red	9033967 Blu	e 9033986 Grey	9033986 Grey 9033989 Violet 9033973 Yellow 9033977 Orange	
No marking on the cable jacket					9033951 Black	9033961 Wh	nite 9033973 Yellow		
					9033955 Brown	9033970 Gre	een 9033977 Orange		
						Characteristic	CS	Customer Approve	
Applications					Test Item		Standard Value		
Internal Wiring, where not subjected to movement or					Test Material		PTFE(ROHS)		
mechanical damage					Insulation resistance(20℃ MΩ*m		1000		
					Vol. Tesr(AC.V.60S) (V)		2000	Cool 9 Ctown	
					Flammability Test		Horizontal flame	Seal & Stamp	
Revisions					Max.DC Resistance(20℃ Ω/km)		208.66(MAX)		
Version	Description	Drawn by	Approved by	Date					
1 0	New document issue	Danniel	Jason	05/10/2015					
								Signature:	
								Date:	
		<u> </u>			Ш				