

DE1DS1

TeSys LE - enclosure for DOL starter - with 2 pushbuttons



Main

Range of product	TeSys
Device short name	DE1D
Product or component type	Enclosure
Material	Polycarbonate
Device composition	Thermal overload relay ordered separately Contactor ordered separately
Product compatibility	LE1D09 LE1D12
Control type	Push-button start green I Push-button stop/reset red O

Complementary

Cable entry number	2 cable entry :ISO20 top 2 cable entry :ISO20 bottom 2 cable entry :Pg 13 bottom 2 cable entry :Pg 16 bottom
Height	88 mm
Width	166 mm
Depth	128.5 mm
Product weight	0.3 kg

Environment

IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Ambient air temperature for operation	-5...40 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0817 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.