

# LC1R80Q5N

Contacteur, EasyPact TVR, 3P, 1NO  
+ 1NC, 37kW, 80A, 380V AC coil



## Main

|                                |                                                                                                                   |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Range                          | EasyPact                                                                                                          |
| Product name                   | EasyPact TVR                                                                                                      |
| Product or component type      | Contacteur                                                                                                        |
| Device short name              | LC1R                                                                                                              |
| Contacteur application         | Reversing<br>Resistive load<br>Motor control                                                                      |
| Utilisation category           | AC-1<br>AC-3                                                                                                      |
| Poles description              | 3P                                                                                                                |
| Power pole contact composition | 3 NO                                                                                                              |
| [Ie] rated operational current | 80 A (at <40 °C) at <= 400 V AC AC-3 for power circuit<br>125 A (at <40 °C) at <= 400 V AC AC-1 for power circuit |
| [Uc] control circuit voltage   | 380 V AC 50 Hz                                                                                                    |
| Auxiliary contact composition  | 1 NO + 1 NC                                                                                                       |
| [Ue] rated operational voltage | Power circuit: 690 V AC 50 Hz<br>Signalling circuit: 690 V AC 50 Hz                                               |

## Complementary

|                                             |                                                                                                                                                                                                                                                 |
|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Motor power kW                              | 22 kW at 220/230 V AC 50 Hz<br>37 kW at 380/400 V AC 50 Hz<br>45 kW at 660/690 V AC 50 Hz                                                                                                                                                       |
| Electrical durability                       | 0.6 Mcycles 80 A AC-3 at Ue <= 440 V                                                                                                                                                                                                            |
| Mechanical durability                       | 6 Mcycles                                                                                                                                                                                                                                       |
| Maximum operating rate                      | 750 cyc/h 40 °C                                                                                                                                                                                                                                 |
| Operating time                              | 20...35 ms closing<br>6...20 ms opening                                                                                                                                                                                                         |
| Control circuit voltage limits              | Drop-out: 0.3...0.6 Uc<br>Operational: 0.8...1.1 Uc                                                                                                                                                                                             |
| Hold-in power consumption in VA             | 36.6 VA cos phi 0.3                                                                                                                                                                                                                             |
| [Ith] conventional free air thermal current | 10 A (at 40 °C) for signalling circuit<br>125 A (at 40 °C) for power circuit                                                                                                                                                                    |
| Average impedance                           | 0.8 mOhm - Ith 110 A 50 Hz for power circuit                                                                                                                                                                                                    |
| Power dissipation per pole                  | AC-3: 5.1 W<br>AC-1: 12.5 W                                                                                                                                                                                                                     |
| Heat dissipation                            | 6...10 W at 50 Hz                                                                                                                                                                                                                               |
| Irms rated making capacity                  | 800 A 380 V AC power circuit AC-3 IEC 60947<br>800 A 380 V AC power circuit AC-3 GB 14048                                                                                                                                                       |
| Rated breaking capacity                     | 640 A at 380 V for power circuit AC-3 conforming to IEC 60947<br>640 A at 380 V for power circuit AC-3 conforming to GB 14048                                                                                                                   |
| [Icw] rated short-time withstand current    | 100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit<br>640 A 40 °C - 10 s for power circuit<br>320 A 40 °C - 1 min for power circuit<br>135 A 40 °C - 10 min for power circuit |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Associated fuse rating        | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>200 A gG at ≤ 690 V coordination type 1 for power circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Overvoltage category          | III                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| [Ui] rated insulation voltage | Power circuit: 690 V conforming to IEC 60947-4-1<br>Signalling circuit: 690 V conforming to IEC 60947-1<br>Power circuit: 690 V conforming to GB 14048.4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Coil technology               | Without built-in suppressor module                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Auxiliary contacts type       | Type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>Type mirror contact 1 NC conforming to IEC 60947-4-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Signalling circuit frequency  | 50 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Minimum switching current     | 5 mA for signalling circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Switching voltage             | 17 V for signalling circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Non-overlap time              | 1.5 Ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Insulation resistance         | > 10 MOhm for signalling circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Mounting support              | Plate<br>Rail                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Connections - terminals       | Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 1 1...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Power circuit: screw clamp terminals 1 4...50 mm <sup>2</sup> - external diameter: 16 mm - cable stiffness: flexible without cable end - busbar cross section: 3 x 16 mm<br>Power circuit: screw clamp terminals 2 4...25 mm <sup>2</sup> - external diameter: 16 mm - cable stiffness: flexible without cable end<br>Power circuit: screw clamp terminals 1 4...50 mm <sup>2</sup> - external diameter: 16 mm - cable stiffness: flexible with cable end<br>Power circuit: screw clamp terminals 2 4...16 mm <sup>2</sup> - external diameter: 16 mm - cable stiffness: flexible with cable end<br>Power circuit: screw clamp terminals 1 4...50 mm <sup>2</sup> - external diameter: 16 mm - cable stiffness: solid without cable end<br>Power circuit: screw clamp terminals 2 4...25 mm <sup>2</sup> - external diameter: 16 mm - cable stiffness: solid without cable end |
| Tightening torque             | Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>Power circuit: 9 N.m - on screw clamp terminals - with screwdriver flat Ø 6 to Ø 8 mm M6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Height                        | 127 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Width                         | 85 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Depth                         | 121 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Standards                     | GB 14048.4<br>IEC 60947-4-1<br>IEC 60947-1<br>GB 14048.1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Product certifications        | CCC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## Environment

|                                                       |                                                                                                                                                                                                                                                                                                    |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pollution degree                                      | 3                                                                                                                                                                                                                                                                                                  |
| Protective treatment                                  | TH conforming to IEC 60068-2-30                                                                                                                                                                                                                                                                    |
| Ambient air temperature for operation                 | -5...40 °C                                                                                                                                                                                                                                                                                         |
| Ambient air temperature for storage                   | -40...60 °C                                                                                                                                                                                                                                                                                        |
| Permissible ambient air temperature around the device | -20...55 °C at Uc                                                                                                                                                                                                                                                                                  |
| Operating altitude                                    | 2000 m without derating                                                                                                                                                                                                                                                                            |
| Fire resistance                                       | 850 °C conforming to IEC 60695-2-11                                                                                                                                                                                                                                                                |
| Mechanical robustness                                 | Vibrations contactor open (1.2 gn, 5...300 Hz) conforming to IEC 60068-2-6<br>Vibrations contactor closed (2.5 Gn, 5...300 Hz) conforming to IEC 60068-2-6<br>Shocks 11 ms contactor open (4 gn) conforming to IEC 60068-2-27<br>Shocks 11 ms contactor closed (6 Gn) conforming to IEC 60068-2-27 |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 15 cm    |
| Package 1 Width              | 11.1 cm  |
| Package 1 Length             | 16 cm    |
| Package 1 Weight             | 1538.7 g |

## Offer Sustainability

|                            |                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                           |
| REACH Regulation           |  <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant with Exemptions                                                                                                       |
| Toxic heavy metal free     | Yes                                                                                                                             |
| Mercury free               | Yes                                                                                                                             |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |
| Circularity Profile        |  <a href="#">End Of Life Information</a>       |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins     |