Geberit Mapress seal ring, CIIR, black



Example image

APPLICATION PURPOSES

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For service water and process water
- For grey and black water with a pH value ≥ 5.5
- For extinguishing water (wet)
- For sprinklers (wet)
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)

CHARACTERISTICS

- Silicone-free (LABS-free)

TECHNICAL DATA

Operating temperature	-30 – +120 °C
Product material	CIIR

Art. no.	DN	d, ø mm
These articles are suitable for the following system: **Geberit Mapress Stainless Steel**		
90401	10	12
90402	12	15
90403	15	18
90404	20	22

Art. no.	DN	d, ø mm
90405	25	28
90406	32	35
90407	40	42
90408	50	54
90409	65	76.1
90410	80	88.9
90411	100	108
These articles are suitable for the following system: **Geberit Mapress Carbon Steel**		
90401	10	12
90402	12	15
90403	15	18
90404	20	22
90405	25	28

Art. no.	DN	d, ø mm
90406	32	35
90407	40	42
90408	50	54
90412	65	66.7
90409	65	76.1
90410	80	88.9
90411	100	108
These articles are suitable for the following system: **Geberit Mapress CuNiFe**		
90401	10	12
90402	12	15
90403	15	18
90404	20	22
90405	25	28

Art. no.	DN	d, ø mm
90406	32	35
90407	40	42
90408	50	54
90409	65	76.1
90410	80	88.9
90411	100	108
These articles are suitable for the following system: **Geberit Mapress Therm**		
90401	10	12
90402	12	15
90403	15	18
90404	20	22
90405	25	28
90406	32	35

Art. no.	DN	d, ø mm
90407	40	42
90408	50	54
90409	65	76.1
90410	80	88.9
90411	100	108
These articles are suitable for the following system: **Geberit Mapress Copper**		
90401	10	12
90402	12	15
90403	15	18
90404	20	22
90405	25	28
90406	32	35
90407	40	42

Art. no.	DN	d, ø mm
90408	50	54