

# BUZZ S3 LOW




STANDARD EN ISO 20345 : 2011



**LEMAITRE**

*Safety since 1974*

**CARBON**  
by LEMAITRE



**Carbon fiber toe-cap**  
Cutting-edge technology from  
the aeronautical industry



**Sizes 35 to 49**

Reference code: **BUZZS30GR**

## Product Highlights



■ **Carbon toe-cap by Lemaitre** : ergonomic build, lightness, similar resistance to steel, athermic and non-magnetic

■ **Memory Foam insole by Lemaitre**: anti-bacterial memory structure, odor neutralizer, MSDs prevention

■ **Retro-reflective side marker**: to signal presence and enhance visibility

■ **Bellows Tongue**: to limit intrusion of dust and stones



■ **Protective toe-cap**: Carbon by Lemaitre



■ **Puncture resistant midsole**: high tenacity fabric "0" penetration



## Anti-static sole CARBON PU2D

■ **Developed outsole for industrial and urban floors**

■ **Large bearing surface**: optimal stability

■ **Shock absorption**: preservation of the back and joints

■ **Conformal to bent positions**: knee notches and crouching

■ **Sculpted studs**: reinforced grip

## USAGE

■ Finishing works, light industry, logistics, services, handling



**lemaitre-securite.com**

An exacting attitude to quality is our culture, safety our priority



# BUZZ S3 LOW



STANDARD EN ISO 20345 : 2011

## Characteristics of the upper

- **Upper material:** breathable water-repellent honeycomb pattern fabric, water-repellent microfiber and retro-reflective marker
- **Bellows tongue:** abrasion-resistant textile
- **Collar :** microfiber
- **Lining:** 3D microporous fabric

## Characteristics of the sole

- **Designation :** CARBON PU2D
- **Material :** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient :**  
forward flat slip: 0,34 (standard  $\geq 0,32$ )  
forward heel slip: 0,31 (standard  $\geq 0,28$ )
- **SRB Adhesion coefficient :**  
forward flat slip: 0,22 (standard  $\geq 0,18$ )  
forward heel slip: 0,20 (standard  $\geq 0,13$ )

## VARIANT



Kendji S3 SRC  
KENDS30BE

## Practical information

Weight of one shoe size 42 : 520 g

**CERTIFICATION N°** 0075/007/161/09/19/2718 EXT 02/10/19

## Packaging

sizes 35 to 42	sizes 43 to 49
<b>shoebox</b> 315 x 220 x 123 mm	<b>shoebox</b> 355 x 220 x 130 mm
<b>carton</b> 635 x 445 x 315 mm	<b>carton</b> 660 x 450 x 360 mm
10 shoeboxes per carton	10 shoeboxes per carton

## Gencods

<b>35</b>	3237154275351	<b>43</b>	3237154275436
<b>36</b>	3237154275368	<b>44</b>	3237154275443
<b>37</b>	3237154275375	<b>45</b>	3237154275450
<b>38</b>	3237154275382	<b>46</b>	3237154275467
<b>39</b>	3237154275399	<b>47</b>	3237154275474
<b>40</b>	3237154275405	<b>48</b>	3237154275481
<b>41</b>	3237154275412	<b>49</b>	3237154275498
<b>42</b>	3237154275429		

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

SBP						
S1						
S1P						
S2						
S3						

200 J toe-cap: protection of the forefoot against impact and crushing

Anti-perforation insert 1100 N: foot protection against perforation

Anti-static footwear	Insulation against cold
Shock absorption at the heel	Insulation against heat
Fuel oil-resistant outsole	Outsole resistance to hot contact
Water penetration and water absorption resistant upper	Water resistant
Electrostatic discharge	Ankle protection

Slip-resistance on ceramic floors with detergent

Slip-resistance on steel floors with glycerol

= +

**Lemaitre Sécurité**  
17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

**lemaitre-securite.com**



Member of  
**SINAMAP**



**DON\_LS 04 TDS 0011**  
Update : 17/02/20