



 PRODUCT-DETAILS

AF580-30-22-68

AF580-30-22-68 24-60V DC Contactor



General Information

Extended Product Type	AF580-30-22-68
Product ID	1SFL617001R6822
EAN	7320500222010
Catalog Description	AF580-30-22-68 24-60V DC Contactor

Long Description	<p>The AF580-30-22-68 is a 3 pole - 1000 V IEC or 600 V UL contactor with pre-mounted auxiliary contacts and Main Circuit Bars, controlling motors up to 315 kW / 400 V AC (AC-3) or 500 hp / 480 V UL and switching power circuits up to 800 A (AC-1) or 750 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (24-60 V DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p>
------------------	---

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

EPLAN Data	9AAC200768_EPLAN
Data Sheet, Technical Information	1SBC100214C0202
Data Sheet, Technical Information (Part 2)	1SAC200017M0002
Instructions and Manuals	1SFC380023-en
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	210 mm
Product Net Depth / Length	242 mm
Product Net Height	283 mm
Product Net Weight	13.6 kg
Dimension Diagram	53540919-60

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	2
Number of Auxiliary Contacts NC	2
Number of Poles	3P
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 800 A
Rated Operational Current AC-1 (I _e)	(1000 V) 40 °C 800 A (1000 V) 55 °C 700 A (1000 V) 70 °C 580 A (690 V) 40 °C 800 A (690 V) 55 °C 700 A (690 V) 70 °C 580 A
Rated Operational Current AC-3 (I _e)	(415 V) 55 °C 580 A (440 V) 55 °C 580 A (500 V) 55 °C 580 A (690 V) 55 °C 500 A (1000 V) 55 °C 250 A (380 / 400 V) 55 °C 580 A (220 / 230 / 240 V) 55 °C 580 A
Rated Operational Current DC-1 (I _e)	(110 V) 1-Pole, 40 °C 800 A (110 V) 2 Poles in Series, 40 °C 800 A (220 V) 3 Poles in Series, 40 °C 800 A (600 V) 3 Poles in Series, 40 °C 800 A (850 V) 3 Poles in Series, 40 °C 800 A
Rated Operational Current DC-3 (I _e)	(110 V) 1-Pole, 40 °C 800 A (110 V) 2 Poles in Series, 40 °C 800 A (220 V) 3 Poles in Series, 40 °C 800 A (600 V) 3 Poles in Series, 40 °C 800 A
Rated Operational Current DC-5 (I _e)	(110 V) 1-Pole, 40 °C 800 A (110 V) 2 Poles in Series, 40 °C 800 A

	(220 V) 3 Poles in Series, 40 °C 800 A (600 V) 3 Poles in Series, 40 °C 800 A
Rated Operational Power AC-3 (P _e)	(415 V) 355 kW (440 V) 355 kW (500 V) 400 kW (690 V) 500 kW (1000 V) 355 kW (380 / 400 V) 315 kW (220 / 230 / 240 V) 160 kW
Rated Breaking Capacity AC-3	8 x I _e AC-3
Rated Making Capacity AC-3	10 x I _e AC-3
Short-Circuit Protective Devices	gG Type Fuses 1000 A
Rated Short-time Withstand Current Low Voltage (I _{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 1300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 4500 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 7000 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 6400 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 3500 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 6000 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 5000 A
Rated Insulation Voltage (U _i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U _{imp}))	Main Circuit 8 kV
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour (AC-2 / AC-4) 60 cycles per hour (AC-3) 300 cycles per hour
Mechanical Durability	3 million
Maximum Mechanical Switching Frequency	300 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U _c Min. ... 1.1 x U _c Max. (at θ ≤ 70 °C)
Rated Control Circuit Voltage (U _c)	60 Hz 24 ... 60 V DC Operation 24 ... 60 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 12 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 12 V·A Holding at Max. Rated Control Circuit Voltage DC 5.5 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 780 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 780 V·A Pull-in at Max. Rated Control Circuit Voltage DC 785 V·A
Power Loss	at Rated Operating Conditions per Pole 32 W
Operate Time	Between Coil De-energization and NC Contact Closing 50 ... 70 ms Between Coil De-energization and NO Contact Opening 53 ... 73 ms Between Coil Energization and NC Contact Opening 45 ... 115 ms Between Coil Energization and NO Contact Closing 50 ... 120 ms
Connecting Capacity Main Circuit	Bar 52 mm ² Bar 50 mm ² Rigid Al-Cable 3x185 mm ² Rigid Cu-Cable 300 mm ² Rigid Cu-Cable 3x185 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Flexible 2x0.75 ... 2.5 mm ² Solid 2 x 1 ... 4 mm ² Stranded 2 x 1 ... 4 mm ²
Connecting Capacity	Bar 52 mm ² Rigid Al-Cable 3x185 mm ² Rigid Cu-Cable 3x185 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Connecting Terminals (delivered in open	M 3.5 (+,-) pozidriv 2 screw with cable clamp

position) Main Poles	
Recommended Screw Driver	Main Circuit M12 Control Circuit Pozidriv 2 Control Circuit M3.5
Tightening Torque	Cable Lug 45 N-m Main Circuit 45 N-m
Terminal Type	Main Circuit: Bars
Suitable for Product Class	Block ContactorsBlock Contactors
Product Name	Block Contactor

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 1000 V
General Use Rating UL/CSA	(1000 V AC) 750 A (600 V AC) 750 A
Horsepower Rating UL/CSA	(200 ... 208 V AC) Three Phase 200 Hp (200 V AC) Three Phase 200 hp (208 V AC) Three Phase 200 hp (220 ... 240 V AC) Three Phase 250 Hp (220 ... 240 V AC) Three Phase 250 hp (440 ... 480 V AC) Three Phase 500 Hp (440 ... 480 V AC) Three Phase 500 hp (550 ... 600 V AC) Three Phase 600 Hp (550 ... 600 V AC) Three Phase 600 hp
Full Load Amps Motor Use	(200 ... 208 V AC) Three Phase 552 A (220 ... 240 V AC) Three Phase 604 A (440 ... 480 V AC) Three Phase 590 A (550 ... 600 V AC) Three Phase 578 A

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C Close to Contactor for Storage -40 ... 70 °C Operation -40 ... 70 °C Storage -40 ... +70 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Shock Direction: A 5 g Shock Direction: B1 5 g Shock Direction: B2 5 g Shock Direction: C1 5 g Shock Direction: C2 5 g

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Declaration	2CMT2021-006277
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

ABB EcoSolutions

End Of Life Disassembling Instructions	1SFC100112M0004
Environmental Product Declaration - EPD	1SFC100109D0201

Certificates and Declarations

ABS Certificate	15-LD1408622-PDA
BV Certificate	BV_13409-C0BV
CB Certificate	SE-82863
CCS Certificate	GB14T00030
CQC Certificate	CQC2007010304256684 CQC2012010304540080
Declaration of Conformity - CCC	2020980304001301 2020980304001045
Declaration of Conformity - CE	2CMT2019-005796
Declaration of Conformity - UKCA	2CMT2020-006118
DNV Certificate	DNV_E-10966
DNV GL Certificate	TAE00001W1
EAC Certificate	9AKK107046A8618
GL Certificate	GL_42988-02HH
LOVAG Certificate	F1107
LR Certificate	16-20064
PRS Certificate	TE_2092_880423_16
RINA Certificate	ELE060313XG_002
RMRS Certificate	9AKK107045A6978
TÜV Certificate	MHM-EST-7.70017788e
UL Certificate	UL_20111101-E36588
UL Listing Card	UL_E36588

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	280 mm
Package Level 1 Depth / Length	375 mm
Package Level 1 Height	310 mm
Package Level 1 Gross Weight	15 kg
Package Level 1 EAN	7320500222010

External Classifications and Standards

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529

IDEA Granular Category
Code (IGCC)

4758 >> lec Contactors

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
1SFN170801R1001	RU19/120 LVRT-Module	RU19/120	1	piece
1SFN170801R1002	RU19/240 LVRT-Module	RU19/240	1	piece

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF580

