

Part Number : 2195620034 Product Description : EXTreme Guardian HD Right-Angle Plug Assembly without Guide Pins, 5 Power Circuits Series Number : 219562 Status : Active Product Category : Board-to-Board Connectors



#### **Documents & Resources**

Drawings 2195620035\_sd.pdf

**3D Models and Design Files** 2195620035\_stp.zip

Specifications 2141130000-PS-000.pdf

## Product Environment Compliance

#### Compliance

| GADSL/IMDS         | Compliant with Exemption 44                       |
|--------------------|---|
| China RoHS         | ®   |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                    |
| REACH SVHC         | Not Contained per D(2024)6225-DC<br>(07 Nov 2024) |
| EU RoHS            | Compliant per EU 2015/863                         |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

## Part Details

## General

| Status         | Active   |
|----------------|--|
| Category       | Board-to-Board Connectors  |
| Series         | 219562   |
| Description    | EXTreme Guardian HD Right-Angle<br>Plug Assembly without Guide Pins,<br>5 Power Circuits |
| Application    | Board-to-Board, Power  |
| Component Type | PCB Header   |
| Product Name   | EXTreme Guardian HD  |
| UPC            | 196823042669   |

## Agency

| CSA | LR19980 |
|-----|---------|
| UL  | E29179  |

## Electrical

| Current - Maximum per Contact | 130.0A |
|-------------------------------|--------|
| Voltage - Maximum             | 125V   |

# Physical

| Breakaway                      | No    |
|--------------------------------|-------|
| Circuits (Loaded)              | 5     |
| Circuits (maximum)             | 5     |
| Color - Resin                  | Black |
| Durability (mating cycles max) | 200   |
| First Mate / Last Break        | No    |
| Flammability                   | 94V-0 |
| Glow-Wire Capable              | No    |
| Guide to Mating Part           | No    |

| Keying to Mating Part          | None                         |
|--------------------------------|------------------------------|
| Lock to Mating Part            | None                         |
| Mated Height                   | 12.74mm                      |
| Material - Metal               | High Conductivity Copper     |
| Material - Plating Mating      | Gold                         |
| Material - Plating Termination | Tin                          |
| Material - Resin               | Liquid Crystal Polymer       |
| Net Weight                     | 21.701/g                     |
| Number of Rows                 | 1                            |
| Orientation                    | Right Angle                  |
| Packaging Type                 | Tray                         |
| PC Tail Length                 | 3.30mm                       |
| PCB Locator                    | No                           |
| PCB Retention                  | None                         |
| PCB Thickness - Recommended    | 1.58mm                       |
| Pitch - Mating Interface       | 5.78mm                       |
| Plating min - Mating           | 0.762µm                      |
| Plating min - Termination      | 2.540µm                      |
| Polarized to Mating Part       | Yes                          |
| Polarized to PCB               | Yes                          |
| (p)ower-(s)ignal Configuration | 5p - 0s                      |
| Temperature Range - Operating  | -40° to +125°C               |
| Termination Interface Style    | Through Hole - Compliant Pin |

# Mates With / Use With

## Mates with Part(s)

| Description   | Part Number       |
|---|-------------------|
| EXTreme Guardian HD Vertical<br>Receptacle Assembly without Guide<br>Receivers, 5 Power Circuits    | 2195630035        |
| EXTreme Guardian HD Right-Angle<br>Receptacle Assembly without Guide<br>Receivers, 5 Power Circuits | <u>2195640035</u> |

This document was generated on Jan 30, 2025