

## Datasheet: Validate Network Connectivity in Less Than 10 Seconds-China

### Key features include:

- Quick and simple to use
- Understand if a network connectivity issue is in the PC or the network and if it's the network, where
- Zero touch reporting automatically sends every test to Link-Live Cloud Service saving time and ensuring accuracy in reporting
- Priced to fit every IT budget as a personal tool everyone can have allowing teams to solve problems faster without the need for a shared device



Robert Barker, Enterprise Systems Coordinator, Lebanon R-III School District. Read his success story at [flukenetworks.com/LinkSprinter](http://flukenetworks.com/LinkSprinter)



LinkSprinter is a pocket-sized Ethernet tester that provides complete end-to-end network connectivity testing and automated cloud based reporting all with the touch of a button. LinkSprinter is used by PC help desk, front line technicians, network engineers and many others, to validate network connectivity, cable, and that power is correctly being applied to PoE powered devices.

Simply connect an Ethernet cable and the LinkSprinter goes to work checking the connection path from wall jack to internet and in less than 10 seconds, you'll know that status of the connection path through color coded LEDs.



LinkSprinter Awards

## Big Things Come In Small Packages

Don't let LinkSprinter's small stature fool you, it's packed with capability and provides several custom configuration options that can be set per tester or within Link-Live Cloud Service Job Pro and the setting is pushed to all units enabling better workforce automation.

LinkSprinter runs a series of standardized tests to ensure consistency in workflow and documentation across team members regardless of skill level.

- **Power Over Ethernet (PoE)**

Check to make sure you can power a phone, security camera or Access Point through a specific port. The LinkSprinter Network Tester can even run without batteries on PoE.

- **Link to the Switch**

Perform a switch test, which indicates switch name, model, slot, port and VLAN you are connected to using CDP/LLDP/EDP. Know your available speed and duplex settings.

- **DHCP Connection**

Confirm that the DHCP server is running and responsive. Request an IP address, get your subnet information, and identify the default gateway and DNS server.

- **Gateway Connection**

Verify the gateway/router address and reachability by pinging the device.

- **Internet Connection**

Confirm cloud connectivity or internal service reachability. Verify DNS server lookup and application port connectivity.

## Quick Answers to Common Tasks

- **Moves, Adds, Changes**

Validate proper connectivity including IP subnet and VLAN so you're ready when devices arrive.

- **PoE Validation**

Ensure switch port provisioning and cabling before installing cameras, phones, or wireless access point.

- **PC Help Desk**

Is the problem in the PC or the Network? If it's the network, find out where so you can escalate with facts.

- **Gateway Connection**

Verify the gateway/router address and reachability by pinging the device.

- **Remote Site Network Connectivity Validation**

Leave one on site, even an office assistant can run a test while the NOC sees the detailed result appear on the Link-Live Cloud Service dashboard.



LinkSprinter 300

LinkSprinter Features by Model	300
Diagnose and test Power over Ethernet (PoE), Link to the switch, DHCP, Gateway, and Internet connection	X
Get VLAN, switch name, and port information via CDP/LLDP/EDP for your managed switches	X
Expert network troubleshooting techniques delivered to color graded LEDs	X
All test results are sent to the Link-Live Cloud Service	X
Get detailed test results sent directly to your email	X
Access your test results through your phone's browser by connecting to the built-in Wi-Fi access point	X
See cable fault and distance to open or short	X
Blink light on switch port	X

\*Please note that the LinkSprinter 100 and 200 are not available for China

## RESULT MANAGEMENT OPTIONS

### Link-Live Cloud Service

Once the LinkSprinter is connected to the Link-Live Cloud service, basic network connectivity test results are automatically uploaded to the dashboard for project management and reporting. This internet-hosted service is available from anywhere at any time using any device with a browser and internet connection. It is especially useful for managers of remote teams that need visibility to test results instantly. In addition, teams that utilize companions to the LinkSprinter, such as the LinkRunner AT, AirCheck G2, or OneTouch AT have a single dashboard system to manage results from network connectivity tests.

Time	Test	P/E	Link	Access	Gateway	WWW
Feb 25, 16 Thursday 5:10:53pm	Name: Shamree Howard's AirCheckG2 MAC: 00C017350086 Device: AirCheckG2 Test Type: wireless Auth Test: 674629e-ebde-11e5-9409-ba5424b09e Images: Comments:		PHY Data Rate: 48 Retry Rate: 0 Signal (dBm): -52 Noise (dBm): -96 SNR (dB): 44	SSID: Cisco4400 AP Name: Cisco1130-1Nort BSSID: 00:17:07:79:00:00 Channel: 11 802.11 Type: bg	IP: 10.250.9.225 Server: 10.250.8.2 Subnet: 255.255.254.0 DNS1: 10.250.1.221 DNS2: 10.250.1.223 DNS3: 129.196.196.25 DNS2 Ping (ms): ---	IP: 10.250.8.1 PING (ms): 18, 7, 7 Public IP: 74.202.20.243 URL: www.google.com PING IP: 216.58.217.36 Time (ms): 11, 10, 13
Feb 25, 16 Thursday 5:03:25pm	Name: Shamree Howard's AirCheckG2 MAC: 00C017350086 Device: AirCheckG2 Test Type: ethernet Images: Comments: Meeting Room Colorado	47v	Speed: 1000 Adv Speed: 10/100/1000 Duplex: FDx Adv Duplex: 100x/FDx	Name: COS_DEV_SW1_flet.eng Model: cisco WS-C3750G-48PS IP/MAC: 10.250.0.2 Port: GigabitEthernet1/0/38 VLAN: 500	IP: 10.250.1.151 Server: 10.250.0.2 Subnet: 255.255.254.0 DNS1: 10.250.1.223 DNS2: 129.196.132.244	IP: 10.250.0.1 PING (ms): 21, 3, 2 Public IP: 74.202.20.243 URL: www.google.com PING IP: 216.58.217.36 Time (ms): 3, 3, 3
Feb 25, 16 Thursday 1:03:23pm	Name: Shamree Howard's AirCheckG2 MAC: 00C017350086 Device: AirCheckG2 Test Type: wireless Images: Comments:		PHY Data Rate: 48 Retry Rate: 2 Signal (dBm): -49 Noise (dBm): -96 SNR (dB): 47	SSID: Cisco4400 AP Name: Cisco1130-1Nort BSSID: 00:17:07:79:00:00 Channel: 11	IP: 10.250.9.225 Server: 10.250.8.2 Subnet: 255.255.254.0 DNS1: 10.250.1.223 DNS2: 129.196.196.25 DNS3 Ping (ms): ---	IP: 10.250.8.1 PING (ms): 11, 6, 3 URL: www.google.com PING IP: 216.58.217.36 Time (ms): 5, 4, 4
Sep 25, 15 Friday 12:32:51pm	Name: Shamree's LinkSprinter 300 MAC: 00C017523713 Device: LinkSprinter Folder: Spiceworks Images: Comments: Spiceworks	48v	Speed: 100 Adv Speed: 10/100 Duplex: FDx Adv Duplex: 100x/FDx RX Pair: 1,2 Polarity: Normal	Name: NETGEAR ProSafe Main Type: LDP Model: Netgear Gigabit Smart Switch IP/MAC: 192.168.0.107 Port: g1/switch Port 1	IP: 192.168.0.100 Server: 192.168.0.1 Subnet: 255.255.255.0 DNS: 192.168.0.1	IP: 192.168.0.1 PING (ms): 1, 2, 1 Public IP: 107.77.100.125 URL: www.google.com 80 IP: 74.125.227.210 Time (ms): 39, 350, 98
Sep 25, 15 Friday 12:28:20pm	Name: Shamree's LinkSprinter 200 MAC: 00C0175209AE Device: LinkSprinter Folder: Spiceworks Images: Comments: Spiceworks	47v	Speed: 1000 Adv Speed: 10/100/1000 Duplex: FDx Adv Duplex: 100x/FDx RX Pair: A3 Polarity: Normal	Name: Test Drive Switch Type: LDP Model: Netgear Gigabit Smart Switch IP/MAC: 192.168.0.00153 Port: g1/switch Port 5	IP: 192.168.0.137 Server: 192.168.0.1 Subnet: 255.255.255.0 DNS: 192.168.0.1	IP: 192.168.0.1 PING (ms): 1, 1, 1 Public IP: 107.77.100.125 URL: www.google.com 80 IP: 173.194.121.18 Time (ms): 26, 131, 95
Sep 25, 15 Friday 12:02:29pm	Name: Shamree's LinkSprinter 300 MAC: 00C017523713 Device: LinkSprinter Folder: Spiceworks Images: Comments:	48v	Speed: 100 Adv Speed: 10/100 Duplex: FDx Adv Duplex: 100x/FDx RX Pair: 3,6	Name: NETGEAR ProSafe Main Type: LDP Model: Netgear Gigabit Smart Switch IP/MAC: 192.168.0.00197 Port: g1/switch Port 1	IP: 192.168.0.100 Server: 192.168.0.1 Subnet: 255.255.255.0 DNS: 192.168.0.1	IP: 192.168.0.1 PING (ms): 1, 1, 1 Public IP: 107.77.100.125 URL: www.google.com 80 IP: 216.58.218.100 Time (ms): 291, 100, 275

Link-Live dashboard

## Technical Specifications

Environmental	
<b>Operating Temperature and Relative Humidity</b>	32°F to 122°F (0°C to 50°C ), Relative Humidity 5% to 90% Non-condensing
<b>Storage Temperature</b>	-4°F to 140°F (-20°C to 60°C)
<b>Shock and Vibration</b>	Random 2g, 5 Hz – 500 Hz (class 2), 1 m drop
<b>Safety</b>	CAN/CSA-C22.2 No. 61010-1-12, UL Std. No. 61010-1 (3rd Edition), IEC61010-1:2010, Pollution degree 2
<b>Altitude</b>	Operating: 13,123 ft. (4,000 m) Storage: 39,370 ft. (12,000 m)
<b>EMC</b>	EN 61326-1:2006
<b>Certifications and Compliance</b>	Conforms to relevant European Union directives Conforms to relevant Australian standards Listed by the Canadian Standards Association Conforms to relevant FCC standards

General	
<b>Dimensions</b>	4.36" x 1.6" x 1.28" (11.07 cm x 4.06 cm x 3.25 cm)
<b>Weight with batteries</b>	Model 100: 0.250 lb (0.113 kg) Model 200/300: 0.255 lb (0.116 kg)
<b>Battery</b>	2 AA Alkaline

Wi-Fi Access Point (Model 200 and 300)	
<b>Specification Compliance</b>	IEEE 802.11b/g
<b>Frequency Channels</b>	802.11 Channels 1 thru 11 default is 11
<b>Operating Frequency</b>	2.412 ~ 2.484 GHz, ISM Band
<b>Regulatory Domain</b>	EN 301 489-1/17
<b>Browser</b>	Internet Explorer 9.0, Firefox 3.6, Chrome 5.0, Safari 5.1 (minimum revision)

## Ordering Guide

Item Name	Description
<b>LSPRNTR-100</b>	Includes 1 LinkSprinter 100, wrist strap, Link-Live Cloud Service Essentials
<b>LSPRNTR-100-10PK</b>	Includes 10 LinkSprinter 100's for the price of 9, wrist straps, Link-Live Cloud Service Essentials
<b>LSPRNTR-100-5PK</b>	Includes 5 LinkSprinter 100's at a reduced price, wrist straps, Link-Live Cloud Service Essentials
<b>LSPRNTR-200</b>	Includes 1 LinkSprinter 200, wrist strap, Link-Live Cloud Service Essentials
<b>LSPRNTR-200-10PK</b>	Includes 10 LinkSprinter 200's for the price of 9, wrist straps, Link-Live Cloud Service Essentials
<b>LSPRNTR-200-5PK</b>	Includes 5 LinkSprinter 200's at a reduced price, wrist straps, Link-Live Cloud Service Essentials
<b>LSPRNTR-300</b>	Includes 1 LinkSprinter 300, wrist strap, Link-Live Cloud Service Essentials
<b>LSPRNTR-300-10PK</b>	Includes 10 LinkSprinter 300's for the price of 9, wrist straps, Link-Live Cloud Service Essentials
<b>LSPRNTR-300-5PK</b>	Includes 5 LinkSprinter 300's at a reduced price, wrist straps, Link-Live Cloud Service Essentials
<b>LSPRNTR-HOLSTER</b>	Belt attachable holster carries one LinkSprinter and includes short patch cable and business card holder
<b>LINKSOLUTIONS-KIT</b>	Includes 1 LinkRunner AT 2000 with standard components, 2 LinkSprinter 300's, 2 LinkSprinter Holsters, Link-Live Cloud Service Essentials

For a complete listing of LinkSprinter models and accessories, visit: [www.enterprise.netscout.com/enterprise-network/network-testing/linkssprinter](http://www.enterprise.netscout.com/enterprise-network/network-testing/linkssprinter)