

## Features

- Functions as a deterrent and an informative tool, promoting safety awareness and preventing accidents.
- Designed to act as a visual warning to others, enhancing awareness of lockout conditions.
- Writable surface allows for quick customization with a marker pen to communicate critical safety information.
- Constructed from 0.7mm tear-proof material, ensuring durability even in harsh environments.
- Can be directly attached to lockout devices or secured using nylon cable ties, allowing flexibility in use.

## RS PRO Safety Lockout Tags

RS Stock No.: 0441220



RS PRO is the own brand of RS. The RS PRO Seal of Approval is your assurance of professional quality, a guarantee that every part is rigorously tested, inspected, and audited against demanding standards. Making RS PRO the Smart Choice for our customers.

## Product Description

- *Lockout tags act as both a deterrent and an informative tool, promoting safety awareness and accident prevention in the workplace.*
- *DANGER TAG is designed for individual workers on equipment, acting as a visual warning to others.*
- *Their easily writable surface allows quick and clear communication of crucial safety information, including the nature of ongoing work, the person responsible, and the expected duration of the lockout.*
- *The surface of the tags is suitable for writing on with a marker pen, allowing for easy customisation.*
- *Can be attached directly to lockout devices or secured with nylon cable ties for convenience and versatility.*
- *Our 0.7mm tags are tear-proof, ensuring their longevity even in demanding environments.*

## General Specifications

Type	Lockout Tags
Material	Made from 0.7mm thick high impact, flexible polyvinyl sheets with Brass eyelets.
Package	1 Set of 5 Nos.
Colour	Black, Red on White

## Mechanical Specifications

Dimensions	145mm X 80mm
Width	80mm
Height	145mm
Tag thickness	0.7mm Thickness
Weight	60 grams

## Operation Environment Specifications

Withstand temperature	-20°C to 60°C
-----------------------	---------------