
pressure regulator LR-1/4-D-7-O-I-MIDI Part number: 192319 Classic - do not use for new projects

With increased return exhaust, working pressure up to 7 bar. Modern alternatives can be found by entering the first four characters of the type code in the search field.



Data sheet

Feature	Value
Size	Midi
Series	D
Actuator lock	Rotary knob with lock
Assembly position	Any
Design structure	directly-controlled diaphragm regulator
Controller function	Output pressure constant
	with initial pressure compensation
	with secondary exhaust
	with return flow
Pressure gauge	Prepared for G1/4
Operating pressure	0 16 bar
Pressure regulation range	0.5 7 bar
Max. pressure hysteresis	0.2 bar
Standard nominal flow rate	2,200 l/min
Maritime classification	see certificate
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
	Inert gases
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further
	operation)
Air purity class at output	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
	Inert gases
Medium temperature	-10 60 °C
Ambient temperature	-10 60 °C
Product weight	660 g
Mounting type	Front panel installation
	Line installation
	with accessories
Pneumatic connection, port 1	G1/4
Pneumatic connection, port 2	G1/4
Materials note	Free of copper and PTFE
	Conforms to RoHS
Material of connecting plate	Zinc die-casting
Material seals	NBR
Material housing	Zinc die-casting



FESTO