

## **Datasheet**

RS PART NUMBER: 8850844

Product Discription: Cable ZYRAD 500 0.75MM SQ

Specification No.: UL3289 19AWG

Customer's Name:

**Customer Approve** 

Description			Construction		
Rated Voltage:	600V	Conductor	Stranded Tinned Copper		
Rated Temperature:	150℃	Size(AWG)	19		
Reference Standard:	UL758,UL1581	Construction(±0.008mm)	24/0.2		
Cross Section		Stranded Dia.(mm)Ref.	1.13		
		Insulation Material	XL-PE		
		Insulation Color	Black		
		Ave Thickness(mm)	0.8		
		Insulation Dia.(±0.15mm)	2.74		
Marking		Remark:	Remark:		

E148000 AWM STYLE 3289 19AWG 150°C 600V VW-1 --- cAL AWM I A 150°C 600V FT1 -F- - LF- PC10 LTK

**Applications Standard Value** Test Item **Test Material** For use as Motor Leads or Internal Wiring of Appliances. XL-PE(ROHS) Max.DC Resistance(20°C Ω/km) 29.3(MAX) Vol. Tesr(AC.V.60S) (V) 2000 Seal & Stamp Flammability Test VW-1 **Revisions** Approved by Version Description Drawn by Date New document issue Lisa 07/07/2015 Jason Signature: Date:

**Characteristics** 

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.