



1km Pi Radio Link

- Plug 'n' Play RF Modem Link
- Direct Cable Replacement
- Range upto 1KM
- Host Data Rate to 38K4
- RF Data Rates to 115Kbps
- 8 User Selectable Channels
- 868MHz CE Compliant for European Licence Free Use
- 100mW Transmit Power (+20dBm)
- Receiver Sensitivity -121dBm



Applications

- USB Cable Replacement
- M2M Communications
- Remote Networking

The PI Dongle radio Modem is a simple to use and very versatile. It will communicate directly with our BLIZZARD Radio Modem and ZULU Radio Modules to provide a PC / Raspberry Pi interface to RF Gateway

Operation Modes

One-to-One operation; for point to point cable replacement comms

Broadcast Mode; where a single master, addresses many Modems concurrently. (Using many Modems set to the same address),

One-to-Many; a network consisting a master and many slaves (the receivers all have the same address)

Many-to-One; where the transmitters all send to a single receiver address.

Part No	Description
RADIOPI	Radio Modem 868MHz +20dBm

PI Dongle Radio Modem



Product Overview

This product is Plug and Play, Connect the antenna to the SMA connector and plug into a USB port.



Power

Power is supplied directly from the USB port

Tx / Rx LED

The LED's operates whenever there is RF activity.

Operating Modes

Each Modem has its own preset address. This is user set during configuration. Any data received is examined and the address header embedded within the data packet is compared with its address. Only data received with matching address will be processed and output to the host, all other data will be discarded.

All Modems are shipped with a default address of 7E7E7E.

The Modem contains an on-board data buffer equal to two data packets. Therefore if RTS is asserted (then the host is unable to receive data) the module will store a max of two data packets, all further data packets received will be discarded.

Normal Operation : Modem is 'Online' automatically transmitting and receiving data from its host and across the RF network.

Configuration Mode: In Configuration mode the Modem can receive a number of commands and the internal registers can be preset to control its operation. In this mode the MODEM is 'Offline' and cannot send or receive RF data.

Possible Modes of Operation:

One-to-One operation; for point to point data communication

1. Plug in the PI Dongle to a PCB or host via USB
2. Set the Addresses for both modems to the same
3. The Two Modems will provide wire replacement comms link

One-to-Many; A network consisting a master and many slaves (the Slave Modems each have a unique address and the Master Modem addresses each Slave individually)

Broadcast operation; where a single 'master' MODEM addresses many 'slave' MODEMS concurrently. (using all PI MODEM modules set to the same address), There is no acknowledgement.

PI Dongle Radio Modem



Host Terminal Software

Any Terminal emulation program can interface the Eval board, one we have found to be easy to use and powerful is 'Terminal' This can be downloaded from :

<https://sites.google.com/site/terminalbpp/>

Ping Pong Mode

This test mode is built into the modem to enable two modems to ping pong signals to each other and report the (RSSI) on the originating modem. To initiate Ping Pong;

1. Connect Modems to Host PC USB Ports
2. Run Terminal Emulation program
3. Determine the USB port Modem is connected to (from Device Manage under Computer Properties)
4. Set the Terminal emulation to 'port' as above, 8, n, 1, CTS/RTS,
5. Enter AT mode by sending '+++'
6. Send the character 'P' from one modem. This Modem will now Ping and report back the reply with RSSI indication

RF Channel Selection 868MHz version

The EU standard sets maximum power transmission limits dependent on frequency, bandwidth and application. Please check the relevant standards are being met when implementing your Application. A rough guidance applicable to the PI channel numbers is given below

Channel Number	Frequency Centre (MHz)	EU Power Allowance mW / dBm	Notes
0	868.400	25 / 14	Applicable standard - EN300-220
1	868.900	25 / 14	
2	869.450	100 / 20	
3	869.600	100 / 20	
4	869.800	25 / 14	

PI Dongle Radio Modem



Configuration Mode (offline)

Commands can be set using a standard Terminal program or by sending the relevant ASCII characters.

Each Command must be followed by the Carriage Return <CR> or 'Enter'

Note All commands are entered in upper case

Command	Description	Response from Zulu
+++	<p>Enter Configuration Mode</p> <p>Note: these must be sent as a string with no char in front or behind this is to ensure that the +++ is not mistakenly received in mid data.</p>	Pi responds with Status
?	retrieve the current register values	Pi responds with all Register Values
F	<p>set factory defaults;</p> <p>R1=7F7F7F R2=7F7F7F R3 = Ch2 (869.450MHz) R4 = 7 (+20dBm) R5 = 1 (19K2)</p>	'OK'
H	Help	Brief description of commands available
P	<p>Ping Mode This sends a ping request .</p> <p>On receiving, the recipient Pi Modem will respond with its address and the level of RSSI (Received Signal Strength) The Ping command is continuously repeated every 1 second until any command or character is entered.</p>	<p>The originating Pi Modem will respond with the Recipient Pi Modems' response, eg. Received from 7F7F7F (D5)</p> <p>Where 7F7F7F = the recipient Address D5= RSSI</p> <p>RSSI Is a Hex value corresponding to the received signal strength Min = 20hex Max =E0hex</p>
S	Save Configuration	'SAVED'
Q	exit configuration mode and return to online mode	No response

PI Dongle Radio Modem



Register Setting (Configuration Mode)

The internal registers enable various parameters to be controlled.

To set a register type 'R#=x' where # is the register number and x is the value to set

For example, to set the channel to channel 3 type : R3=3<CR>

(Where <CR> is carriage return or enter on the keyboard) The modem will then return 'OK' or 'Error' if an incorrect command is entered. Save the changes by typing S<CR>

The modem will return with 'SAVED'

Default values are shown in **BOLD**

Register	Value Range	Description	Example
R1	0000 - FFFFFFFF (24 bit address)	Sets the recipient Pi MODEM Address	R1=0001 (Data sent is addressed to Pi MODEM with address 0001)
R2	0000 - FFFFFFFF (24 bit address)	Set own Pi Modem address	R2=F001 (Data sent is from Pi MODEM with address F001)
R3	CH0 to CH4	Sets the RF Channel See "RF channel Selection"	R3=2 (Transmit on Channel 2)
R4	0 = +1dBm 1 = +2dBm 2 = +5dBm 3 = +8dBm 4 = +11dBm 5 = +14dBm 6 = +17dBm 7 = +20dBm	Set the RF Transmit Power output*	R4=7 (sets Transmit Power to max)*
R5	0 = 9,600 1 = 19,200 2 = 28,800 3 = 56,000	Set the RF baud rate	R5=3 (sets the RF data rate to 56Kbps)

*Note : Reducing Tx power reduces battery consumption!
Reducing the baud rate will increase the range!

Technical Specifications

Absolute Maximums:

Temperature Range: Storage -50 to +125°C.

Weight: SMT version 7grams, DIP Part 13grams

Electrical Characteristics:

Parameter	Min	Max	Units
Supply Voltage	-0.3	25	V
Voltage on any Input	-0.3	Vcc+0.	V
Max Input power (thro Antenna)		+10	dBm

PI Dongle Radio Modem

DC Characteristics

Parameter	Min	Typical	Max	Units
Supply Voltage	9		25	V
Operating Temperature	-40		+85	°C
Pi Tx Supply Current: When Transmitting		100		mA
When sleeping		1		uA
Pi Rx Supply Current: When Receiving		18.5		mA
When sleeping		1		uA

AC Characteristics

Parameter	Min	Typical	Max	Units
Operating Frequency - 868: see freq channel setting	868		870	MHz
Operating Temperature	-40		+85	°C
Band width per channel		100		KHz
Deviation		45		KHz
Pi Tx MAX Output Power			+20	dBm
Pi Tx—Rx FSK Raw RF Data Rate			256	Kbps
Pi Rx Sensitivity		-116		dBm

RF Solutions Ltd. Recycling Notice

Meets the following EC Directives:

DO NOT Discard with normal waste, please recycle.

ROHS Directive 2002/95/EC

Specifies certain limits for hazardous substances.

WEEE Directive 2002/96/EC

Waste electrical & electronic equipment. This product must be disposed of through a licensed WEEE collection point.

RF Solutions Ltd. , fulfils its WEEE obligations by membership of an approved compliance scheme.

R F Solutions Ltd.,
William Way, Burgess Hill
W. Sussex. RH15 9AG. England.

Email : sales@rfsolutions.co.uk <http://www.rfsolutions.co.uk>

Tel Sales: 01273 898 020 Tel Technical: 01273 898 007

Tel Gen Enq: 01273 898 000

Whilst the information in this document is believed to be correct at the time of issue, RF Solutions Ltd does not accept any liability whatsoever for its accuracy, adequacy or completeness. No express or implied warranty or representation is given relating to the information contained in this document. RF Solutions Ltd reserves the right to make changes and improvements to the product(s) described herein without notice. Buyers and other users should determine for themselves the suitability of any such information or products for their own particular requirements or specification(s). RF Solutions Ltd shall not be liable for any loss or damage caused as a result of user's own determination of how to deploy or use RF Solutions Ltd's products. Use of RF Solutions Ltd products or components in life support and/or safety applications is not authorised except with express written approval. No licences are created, implicitly or otherwise, under any of RF Solutions Ltd's intellectual property rights. Liability for loss or damage resulting or caused by reliance on the information contained herein or from the use of the product (including liability resulting from negligence or where RF Solutions Ltd was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict RF Solutions Ltd's liability for death or personal injury resulting from its negligence.

www.rfsolutions.co.uk

RF Solutions Ltd

Unit 21 Cliffe Industrial Estate, Lewes, East Sussex, United Kingdom, BN8 6JL

Tel. Sales: +44 (0)1273 898 000 • Tech. Support: +44 (0)1273 898 007

