




**Features**

- Through the proven CMOS technology, in connection with the USB 2.0 or USB 3.0 the images are shown quickly and clearly
- These cameras are also ideal for more demanding applications, such as, for example, darkfield, phase contrast and for fluorescence applications
- As well as the camera, the delivery includes our multi-lingual camera software Microscope VIS KERN OXM 901, a USB cable (Length: 2 m) various eyepiece adapters and an object micrometer to calibrate the software
- Please order the appropriate C-mount adapter to fit your KERN microscope now

STANDARD



Model	Resolution	Interface	FPS	Sensor	Sensor size	Colour/ Monochrome	Supported operating system	
<b>KERN</b>								
ODC 822	1,3 MP	USB 2.0	15 – 48	CMOS	1/3"	colour	Win XP, Vista, 7, 8, 10	↓
ODC 824	3,1 MP	USB 2.0	11,5 – 45	CMOS	1/2"	colour	Win XP, Vista, 7, 8, 10	↓
ODC 825	5,1 MP	USB 2.0	6,8 – 55	CMOS	1/2,5"	colour	Win XP, Vista, 7, 8, 10	↓
ODC 831	3,1 MP	USB 3.0	27,3 – 53,3	CMOS	1/3"	colour	Win XP, Vista, 7, 8, 10	↓
ODC 832	5,1 MP	USB 3.0	14,2 – 101,2	CMOS	1/2,5"	colour	Win XP, Vista, 7, 8, 10	↓

↓ Price reduction

C-mount camera – HDMI KERN ODC-85



Scope of supplies

**Features**





















- The ODC-851 HDMI microscope camera has been specially developed for direct HDMI connection to your HDMI compatible display device. The images can also be stored directly onto the SD card delivered with the device
- As an alternative, a USB 2.0 connection is also still available to connect a laptop or PC
- Power supply is from an external 12 V power unit
- Scope of delivery: Camera, software, USB mouse, USB 2.0 cable (Length: 2 m), HDMI cable (Length: 2 m) and SD card (16 GB)
- Please order the appropriate C-mount adapter to fit your KERN microscope now

STANDARD



Model	Resolution	Interface	FPS	Sensor	Sensor size	Colour/ Monochrome	Supported operating system	
<b>KERN</b>								
ODC 851	2 MP	HDMI, USB 2.0, SD	30 – 60	CMOS	1/2,8"	colour	Win XP, Vista, 7, 8, 10	↓

↓ Price reduction

 <b>360°</b>	<b>360° rotatable microscope head</b>	 <b>FL-LED</b>	<b>Fluorescence illumination for compound microscopes</b> With 3 W LED illumination and filter	 <b>WLAN</b>	<b>WLAN data interface:</b> For transmitting of the picture to a mobile display device
 <b>MONO</b>	<b>Monocular Microscope</b> For the inspection with one eye	 <b>PH</b>	<b>Phase contrast unit</b> For a higher contrast	 <b>HDMI</b>	<b>HDMI digital camera</b> For direct transmitting of the picture to a display device
 <b>BINO</b>	<b>Binocular Microscope</b> For the inspection with both eyes	 <b>DF</b>	<b>Darkfield condenser/unit</b> For a higher contrast due to indirect illumination	 <b>SOFTWARE</b>	<b>PC software</b> To transfer the measurements from the device to a PC.
 <b>TRINO</b>	<b>Trinocular Microscope</b> For the inspection with both eyes and the additional option for the connection of a camera	 <b>POLAR</b>	<b>Polarising unit</b> To polarise the light	 <b>AUTO ATC</b>	<b>Automatic temperature compensation</b> For measurements between 10 °C and 30 °C
 <b>ABBE</b>	<b>Abbe Condenser</b> With high numerical aperture for the concentration and the focusing of light	 <b>INFINITY</b>	<b>Infinity system</b> Infinity corrected optical system	 <b>IP</b>	<b>Protection against dust and water splashes IPxx</b> The type of protection is shown by the pictogram.
 <b>HAL</b>	<b>Halogen illumination</b> For pictures bright and rich in contrast	 <b>ZOOM</b>	<b>Zoom magnification</b> For stereomicroscopes	 <b>BATT</b>	<b>Battery operation</b> Ready for battery operation. The battery type is specified for each device.
 <b>LED</b>	<b>LED illumination</b> Cold, energy saving and especially long-life illumination	 <b>PARALLEL</b>	<b>Parallel optical system</b> For stereomicroscopes, enables fatigue-proof working	 <b>RECHARGE</b>	<b>Battery operation rechargeable</b> Prepared for a rechargeable battery operation
 <b>IL</b>	<b>Incident illumination</b> For non-transparent objects	 <b>SCALE</b>	<b>Integrated scale</b> In the eyepiece	 <b>230 V</b>	<b>Mains adapter</b> 230V/50Hz in standard version for EU. On request GB, AUS or USA version.
 <b>TL</b>	<b>Transmitting illumination</b> For transparent objects	 <b>SD</b>	<b>SD card</b> For data storage	 <b>230 V</b>	<b>Power supply</b> Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.
 <b>FL</b>	<b>Fluorescence illumination</b> For stereomicroscopes	 <b>USB 2.0</b>	<b>USB 2.0 digital camera</b> For direct transmitting of the picture to a PC	 <b>1 DAY</b>	<b>Package shipment</b> The time required to manufacture the product internally is shown in days in the pictogram.
 <b>FL-HBO</b>	<b>Fluorescence illumination for compound microscopes</b> With 100 W mercury lamp and filter	 <b>USB 3.0</b>	<b>USB 3.0 digital camera</b> For direct transmitting of the picture to a PC		

## Abbreviations

<b>C-Mount</b> Adapter for the connection of a camera to a trinocular microscope	<b>LWD</b> Long Working Distance	<b>SWF</b> Super Wide Field (Field number at least $\varnothing$ 23 mm for 10 $\times$ eyepiece)
<b>FPS</b> Frames per second	<b>N.A.</b> Numerical Aperture	<b>W.D.</b> Working Distance
<b>H(S)WF</b> High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)	<b>SLR Kamera</b> Single-Lens Reflex camera	<b>WF</b> Wide Field (Field number up to $\varnothing$ 22 mm for 10 $\times$ eyepiece)

## Your KERN specialist dealer: