

Product data sheet

Specifications



Repacked, vertical distribution block, Acti9 VDIS, 3L+N, 125A, 250VAC to 440VAC, 33 outgoing terminals

A9XPK707W



This repackaged option saves 10.848 over the standard condition

Main

Range	Acti9
Product name	Acti9 VDIS
Product or component type	Vertical distribution block
Range compatibility	Pragma Prisma G Prisma Pack 250 Prisma Pack 160 PrismaSeT S

Complementary

Lines description	3L + N
[In] rated current	125 A
[Ue] rated operational voltage	250/440 V
Network type	AC
Network frequency	50/60 Hz
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Number of terminal blocks	1 with 33 outgoing terminals
Connections - terminals	Supply: tunnel type terminals10...35 mm² Distribution: push-in spring terminals1.5...10 mm² (rigid) Distribution: push-in spring terminals4...16 mm² (stranded) Distribution: push-in spring terminals1.5...16 mm² (flexible) Distribution: push-in spring terminals1.5...16 mm² (flexible with ferrule)
Distribution block outgoing terminals	7 holes for per phase 12 holes for neutral
Pollution degree	3
Height	408 mm
Depth	71.5 mm
Width	40.5 mm
Product weight	1.14 kg

Environment

IP degree of protection	IPxx B
-------------------------	--------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 1	1
Package 1 Height	15.000 cm
Package 1 Width	30.000 cm
Package 1 Length	40.000 cm
Package 1 Weight	1.516 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Lower carbon footprint

11 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins