



SECU'SOLV

HIGH SAFETY DEGREASING CLEANING AGENT

1. MAIN CHARACTERISTICS

Cold degreasing, de-oxidiser of high safety contacts

- Flash point = 63°C
- Penetrates the least nooks and crannies extremely rapidly.
- Very high de-oxidising effectiveness.
- Controllable evaporation
- Recommended for cleaning electrical or electronic contacts
- Leaves metals, alloys, paint, rubber and tropicalisation varnish unharmed
- Check the compatibility with fragile plastics.
- Removes oil, grease, dirt and other contaminants.

2. SCOPE OF APPLICATION

- All mechanical parts
- Electronic circuits
- Electronic contacts
- Electrical cabinets
- Relays
- Connectors
- Switches
- Potentiometers

3. DIRECTIONS FOR USE

- DO NOT USE WHEN SWITCHED ON
 - Fill a spray can and spray directly onto the part to be degreased or de-oxidised
 - Usable when tempering
 - Cleaning with a brush
 - Using a compressor (maximum pressure: 3 bars)
 - The evaporation of the SECU'SOLV can be accelerated using a blowgun, compressor or dust remover.
- JELT'R 99.9 Reference: 005033 or by wiping

4. PHYSICOCHEMICAL CHARACTERISTICS

- Appearance: Liquid
- Colour: Orange
- Odour: characteristic
- Density of the PA (20°C): 0.81 g/cm³ +/-0.05

5. PRECAUTION OF USE - LABELLING

Product for professional use. Refer to the safety data sheet.

6. PACKAGING AND STORAGE

Jerrycan of 5L (4 cans / crate). Reference 747505.

Keep it away from light, heat and cold in a well-ventilated area.

Storage temperature: 0°C to 45°C

Safety data sheets are available on the Internet: <http://www.jelt.fr>

FAITES ÉQUIPE AVEC LA PERFORMANCE

This product information was created on 29/09/2016 and cancels all previous information. The information supplied is based on our knowledge and experience to date. Please be aware of the potential risks to users that may occur when the product is used for purposes other than for which it was designed. In no way does this exempt the user from knowing and applying all regulations related to their activity. The product's user is solely responsible for taking the necessary precautions for the product.

ITW Spraytec - 5 bis rue Retrou - 92600 ASNIERES SUR SEINE - Tel. 01.40.80.32.32 Fax 01.40.80.32.40