

## SCHEDA TECNICA

# FEROX PRIMER

## *Primer for “special effects” paints*

**- PRODUCT DESCRIPTION**

**Ferox Primer - Primer for “special effects” paints** is a resin-based product, ideal for enhancing the finish of enamels with special effects.

The application of the primer guarantees perfect adhesion to multiple surfaces such as metal, glass, stone, ceramics of finishing glazes with special effects such as fluorescent, mirror effect or diamond. White in color and with excellent coverage. Self-cleaning valve.

**- HOW TO USE****Surface preparation:**

Thoroughly clean the surface to be treated from rust, dust, grease and grease.

**Application:**

Shake the can vigorously for at least two minutes. Spray from a distance of 25 cm. Apply two or three light, crossed coats. After use turn the can upside down and spray the gas to achieve dispenser cleanliness.

Can be overpainted after 1 h.

Any product stains can be removed with acetone and/or nitro thinner.

**Caution:** Do not use on surfaces that have already been treated with synthetic paints.

On POLYSTYRENE, first apply Ferox Primer for polystyrene and then Ferox Primer for Paints with special effects.

**- SPECIFICATIONS**

|                        |                         |
|------------------------|-------------------------|
| Aspect                 | Aerosol                 |
| Smell                  | Solvent characteristic  |
| Color                  | White                   |
| Surrender              | 0.8 -1.5 m <sup>2</sup> |
| Propellent             | Propane – butane        |
| Temperature resistance | 80°C                    |
| Drying times           |                         |
| Dust-free              | 15 minutes              |
| Dry to the touch       | 30 minutes              |
| Deep dry               | 1 hour                  |

The above data do not constitute specifications and are subject to normal manufacturing tolerances

**- SHELF LIFE**

At least 3 years if stored under the following conditions: in the original packaging and sealed, away from direct sunlight, in a temperature range of 5°C to 35°C.

**- PACKAGING**

Aerosol candy from 400 ml

Code: 2016

**- WARNINGS**

For information on product safety, please consult the Safety Data Sheet. In case of storage or use in conditions other than those indicated, please contact the company

**T.S. 17-12-2024**

The data contained in this printout are the result of technological research in our laboratories and are given for information purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which must be carefully checked by the user.  
We do not accept any responsibility for any technical information or consultancy services provided free of charge by our customer service.  
For information, please contact our Technical Service at 800-016604

AREXONS S.p.A. A SOCIO UNICO

Via Antica di Cassano, 23

20063 Cernusco sul Naviglio (MI) Italy

Share capital: € 15.000.000 I.V.

Milan Business Register no. 09728360968

Tax Code and VAT Number 09728360968

Management and coordination pursuant to Article 2497 of the Italian Civil C

B.V.

Switchboard 02 92436.1

Fax 02 92436.306

www.arexons.com

