



Product: [7731ANH](#)

7731ANH - 75 Ohm SDI Coax, RG-11, 14 AWG Solid BC, Foil + 95% TC Braid, LSZH-C Jkt

Product Description

75 Ohm SDI Coax, RG-11, 14 AWG Solid Bare Copper Conductor, PE Insulation, Foil + 95% Tinned Copper Braid Shield, LSZH Jacket, Dca. IEC 60332-3-24.

Technical Specifications

Product Overview

Suitable Applications:	Digital Video, 6 Gb/s UHDTV, HD-SDI 1080p; The cable is UV-resistant and suitable for indoor and outdoor use
------------------------	--

Construction Details

RG Type:	11
----------	----

Conductor

Number of Element	Size	Stranding	Nom. Diameter	Material
1	14 AWG	Solid	1.63 mm	BC - Bare Copper

Insulation

Element	Material	Nom. Insulation Diameter
Insulated Conductor	PE - Polyethylene (Foam)	7.11 mm (0.280 in)

Outer Shield

Layer	Outer Shield Type	Material	Coverage
1	Tape	Tri-Laminate (Alum+Poly+Alum)	100%
2	Braid	Tinned Copper (TC)	95%

Outer Jacket

Material	Nom. Diameter
LSZH - Low Smoke Zero Halogen (Flame Retardant)	10.2 mm

Electrical Characteristics

Return Loss (RL)

Frequency	Min. Return Loss
5 - 850 MHz	23 dB
850 - 3000 MHz	21 dB

Attenuation

Frequency	Nom. Attenuation
1 MHz	0.5 dB/100m
10 MHz	1.5 dB/100m
71.5 MHz	3.6 dB/100m
135 MHz	4.8 dB/100m
270 MHz	6.9 dB/100m
360 MHz	8 dB/100m
540 MHz	10 dB/100m
720 MHz	11.7 dB/100m
750 MHz	12 dB/100m

1000 MHz	14.1 dB/100m
1500 MHz	18 dB/100m
2250 MHz	22.6 dB/100m
3000 MHz	26.9 dB/100m
4500 MHz	34.1 dB/100m

Electricals

Max. Conductor DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
8.2 Ohm/km (2.5 Ohm/1000ft)	53 pF/m (16 pF/ft)	75 Ohm	84%

Mechanical Characteristics

Temperature

Operating	Installation	Storage
-30°C To +70°C	-5°C To +50°C	-30°C To +70°C

Bend Radius

Stationary Min.
100 mm (3.9 in)

Max. Pull Tension: 650 N (150 lbf)

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor - Euroclass Dca
Flammability / Reaction to Fire:	IEC 60332-1-2 and IEC 60332-3-24, CEI 20-22-3
CPR Compliance:	CPR Euroclass: Dca-s1,d1,a1
ISO/IEC Compliance:	IEC 61034-2 - Smoke Density Min Transmittance = 60%
CENELEC Compliance:	EN 50117-1
European Halogen Free Standards:	IEC 62821-1 Halogen Free Compliance = Yes, IEC 60754-1 - Halogen Amount = Zero, IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity = 2.5 µS/mm, IEC 60754-2 - Halogen Acid Gas Amount - Min. pH = 4.3
European Directive Compliance:	EU CE Mark

History

Update and Revision: Revision Number: 0.216 Revision Date: 01-25-2022

Variants

Item #	Color	Putup Type	Length	EAN
7731ANH.00M30	Black	Reel	30 m	8719605013842
7731ANH.00M50	Black	Reel	50 m	8719605013866
7731ANH.00305	Black	Reel	305 m	8719605013774
7731ANH.00M365	Black	Reel	365 m	8719605013859
7731ANH.00500	Black	Reel	500 m	8719605013781
7731ANH.00600	Black	Reel	600 m	8719605013798
7731ANH.00650	Black	Reel	650 m	8719605013804
7731ANH.00750	Black	Reel	750 m	8719605013811
7731ANH.00800	Black	Reel	800 m	8719605013828
7731ANH.001000	Black	Reel	1,000 m	8719605013750
7731ANH.001219	Black	Reel	1,219 m	8719605013767
7731ANH.051219	Brown	Reel	1,219 m	8719605013989
7731ANH.04500	Cream	Reel	500 m	8719605013972
7731ANH.02500	Green	Reel	500 m	8719605013934
7731ANH.021000	Green	Reel	1,000 m	8719605013897
7731ANH.021219	Green	Reel	1,219 m	8719605013903
7731ANH.022000	Green	Reel	2,000 m	8719605013910
7731ANH.03500	Violet	Reel	500 m	8719605013965
7731ANH.031000	Violet	Reel	1,000 m	8719605013958

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.