

### product type designation

product description

**SM FO CORD SC/BFOC, 9/125**

Singlemode glass fiber-optic cable, preassembled

SM FO Cord SC/BFOC; 9/125, pre-assembled with 1x SC duplex connectors and 1x, BFOC connectors; length 1.0 m.



Figure similar

suitability for use	Cable for applications in the control cabinet
version of the assembled FO cable	Pre-assembled with 1x SC DUPLEX connector and 2x, BFOC connector
cable designation	I-V(ZN)H 2E9/125 G.652D
wire length	1 m
<b>optical data</b>	
attenuation factor per length	
• at 1300 nm / maximum	0.4 dB/km
• at 1550 nm / maximum	0.3 dB/km
<b>mechanical data</b>	
number of fibers / per FOC core	1
number of FO cores / per FOC cable	2
version of the FO conductor fiber	Singlemode glass fiber 9/125 µm
design of the FOC core	Fixed core
outer diameter	
• of the optical fibers	9 µm
• of the optical fiber sheath	125 µm
• of the FOC core sheath	2.8 mm
width / of cable sheath	5.9 mm
thickness / of cable sheath	2.8 mm
material	
• of the fiber-optic cable core	Quartz glass
• of the optical fiber sheath	Quartz glass
• of the FOC core sheath	FR-LSZH
• of the fiber-optic cable sheath	LSZH
• of the strain relief	Aramid fibers
color	
• of the FOC core sheath	green/green
bending radius	
• with single bend / minimum permissible	42 mm
tensile load	
• during installation / short-term	500 N
• during operation / maximum	500 N
continuous shear force per length	100 N/cm
<b>ambient conditions</b>	
ambient temperature	
• during operation	-30 ... +70 °C
• during storage	-30 ... +70 °C

<ul style="list-style-type: none"> <li>during transport</li> <li>during installation</li> </ul>	-30 ... +70 °C -5 ... +50 °C
fire behavior	flame-resistant acc. to IEC 60332-3-22 (Cat. A)
protection class IP	IP20
<b>product features, product functions, product components / general</b>	
product feature	
<ul style="list-style-type: none"> <li>halogen-free</li> <li>silicon-free</li> </ul>	Yes Yes
product component / rodent protection	No
<b>standards, specifications, approvals</b>	
certificate of suitability	
<ul style="list-style-type: none"> <li>RoHS conformity</li> </ul>	Yes
reference code	
<ul style="list-style-type: none"> <li>according to IEC 81346-2</li> <li>according to IEC 81346-2:2019</li> </ul>	WH WHA
<b>further information / internet links</b>	
internet link	
<ul style="list-style-type: none"> <li>to web page: selection aid TIA Selection Tool</li> <li>to website: Industrial communication</li> <li>to website: Industry Mall</li> <li>to website: Information and Download Center</li> <li>to website: Selection guide for cables and connectors</li> <li>to website: Image database</li> <li>to website: CAx-Download-Manager</li> <li>to website: Industry Online Support</li> </ul>	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a> <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="https://sie.ag/2QdlxcP">https://sie.ag/2QdlxcP</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

last modified:

9/2/2023 