


► PRODUCTS → CONNECTION TYPE → PRODUCT MICROSITES → APPLICATIONS → CONTACT US → PRESS ROOM




68602-116HLF 68602-116HLF - BergStik®: Unshrouded Header, Through Hole, Double Row, 16 Positions, 2.54 mm Pitch, Vertical, 5.84 mm (0.23 in.) Mating, 3.81 mm (0.15 in.) Tail







General Dimensional Electrical Mechanical Mounting Physical	Approvals / Certifications Other Features								
General									
Number of contacts (per row)	8								
Number of contacts (Total)	16								
Number of rows	2								
Orientation	Vertical								
Packaging	Bulk Packaging								
Attachment type (Board)	Through Hole								
Series Number	68602								
Dimensional									
Length (Mating pin)	5.84 mm (0.23 in.)								
Length (Overall pin)	12.19 mm (0.48 in.)								
Length (Tail)	3.81 mm (0.15 in.)								
Electrical Current rating	3 amp Continuous								
Resistance (Insulation)	5000 M-ohms								
Voltage rating	1500V AC rms								
Mechanical									
Retention force	8.88N (2 lbf)								
Mounting Retention feature (Board)	No								
	Vapor-phase								
Solder process	IR Reflow Soldering Processes								
	Compatible with Wave								
Physical Color (Housing)	Black								
Material (Contact)	Phospor Bronze								
Material (Housing)	High Temperature Black Thermoplastic								
Plating (Contact area)	0.76 μm (30 μin.) Gold or GXT								
Plating (Tail)	0.76 μm (30 μin.) Gold or GXT, or Tin								
Underplating (Contact)	1.27 µm (50 µin.) Nickel								
Flammability rating	UL 94 V-0								
Temperature (Range)	-65°C to +125°C								
Approvals / Certifications									
UL File Number	E66906								
CSA File Number	LR46923								
Approvals / Certifications	UL and CSA Approved								
Other Features Comments	Sample Kit 950501-016								
Literature	950559-001								
Literature	300003-001								



7. MILIT	ARY BERGSTIK HEADER
P/N	XXXXX-XYY-MIL
NOT	AVAILABLE.

- 8. ±.010/0.25 TOL APPLIES TO ALL "G" TAILS EXCEPT INDICATED PARTS ON TABLE WHERE +.010/0.25 -.000/0.00
- 9. NOTCH CONFIGURATION WILL VARY PER VENDOR'S DISCRETION.
- 10. BERGSTRIP™ PART NUMBERS FOLLOWED BY BY A "B" ARE BULK PRICED.
- 11. TAIL LENGTH (DIM. G) TO BE ±.008/.0.20.
- 12. POSITIONS PER ROW 37 TO 50 CAN BE PRODUCED. BUT FLATNESS AND CURVATURE MAY NOT BE HELD AS CLOSE AS 36 POSITIONS.
- 13. THESE PRODUCTS MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.
- 14. PLATING OPTIONS: PERFORMANCE PLATING WILL BE EITHER GOLD OR GXT ON POST OR TAIL. OPTIONALLY (78~295u"/2~7.5u) TIN ON TAIL.
- 15. "THIS PRODUCT HAS 100% TIN PLATING IN THE INTERFACE AND HAS NOT BEEN TESTED FOR WHISKER GROWTH IN ALL INTERCONNECT **FNVIRONMENTS.**"
- 16. THE OAL DON'T EXCEED 34.5mm
- 17. INCREMENTS BY 0.1mm IN LENGTHS ONLY
- 18. FOR SPECIAL PACKAGING REQUEST PLEASE CONTACT PRODUCT MANAGER FOR AVAILABILIT
- 19. TO DETERMINE DIMENSIONS: N-NUMBER OF ROSITION REP ROW

N=NOWRF!	K OF	PUS	SHIO	N PER ROW	
EXAMPLE:	10 F	POS.	NX	.100/2.54	
				, ,	

mat'l. code					sur	surface /tolerance					pro	jecti	ion	product family																														
NOTE 2 & 3				ISO	ISO 1302 V ISO 406					ا ا	<u> </u>	1	BÉRGSTIK																															
Itr	ecr	n no	dr	date	toler	nce	s unless				7		ユ	title	:																													
DG					ang	۵0					.XX±01/.X±.3																						INC	CH/I	мм	l R	FR	GSTI	K II	HF	ADE	R	D/R	
					ung	-	linear									_		_							•																			
					O°±	2.		XXXX:	.XXXX±0020/.XXX±.051			le 2	2:1		. 11	JU/ .	2.54	+CC	STF	KAIC	, H I																							
					dr	T.	.BREWBA	EWBAKER 12/21/94 HANNA 12/21/94 MURPHY 12/21/94				-	_	dwg	nc)		5	sheet	t 2	of 8	size																						
					engr	╚	T.HANN					FCj	, Ī.	67996						Аз																								
					chr		J.MURPI			URPHY 12/21/94				7)		<u> </u>				7330			П3																					
					арр	1	T.HANN	Α	12/2	1/94		7		type	;	Proc	duct	Cu	stom	er	Draw	ing																						
she	et	revi	sion																																									
inde	ex	she	et																																									
					4 P	DS	3: Rev	:DO	}		S	TAT	TUS:	Rele	ase	d		Prin	ted:	No	v 16	20																						

NOTES

В

С

XXXXX-5YY

XXXXX-6YY

XXXXX-7YY

XXXXX-8YY

XXXXX-9YY

XXXXX-0YY

1. PART NUMBER OPTIONS: PIN PLATING CODES (SEE ABOVE)

HIGH TEMPERATURE MATERIAL:

PART NUMBERS WITH AND WITHOUT "H" WILL BE SUPPLIED WITH HIGH TEMPERATURE PLASTIC.

15u"/0.38u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni

30u"/0.76u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni

30u"/0.76u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni

15u"/0.38u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni

15u"/0.38u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni

30u"/0.76u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni

NUMBER OF POSITIONS:

EVEN NUMBER OF POSITIONS FROM 2 (2X1) THROUGH 72 (2X36). -XOOH INDICATES BERGSTRIP PRODUCT. SÉE PAGE 3 FOR SPECIAL GEOMETRY OF THIS CONTINUOUS STRIP PRODUCT. AUTOMATED REELS WILL CONTAIN 45,000 PINS. SEE SPECIFIC PART NUMBERS FOR AVAILABILITY.

PACKAGING:

PACKAGED IN POLY BAGS.

EIGHT DIGIT PART NUMBERS FOLLOWED BY A "T" ARE PACKAGED IN TUBES. SEE SPECIFIC PART NUMBERS FOR AVAILABILITY.

EIGHT DIGIT PART NUMBERS FOLLOWED BY A "G" ARE PACKAGED IN GPAX FOR IBM ONLY. SEE SPECIFIC PART NUMBERS FOR AVAILABILITY.

PART NUMBERS FOLLOWED BY A "C" ARE PACKAGED IN TUBES WITH A PICKUP CAP APPLIED.

EIGHT DIGIT PART NUMBERS FOLLOWED BY A "A" ARE PACKAGED 10G IN TAPE/REEL WITH PICKUP CAP P/N 95730-003 APPLIED, PER BUS-14-345.

LEAD FREE:

ADD "HLF" SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION, NOT AVAILABLE FOR -5YY, -5YYH, -6YY & -6YYH

2. BODY MATERIAL:

BODY MATERIAL: MANUFACTURER'S OPTION OF NYLON, PCT GLASS FIBER REINFORCED OR MINERAL FILLED LCP FLAME RETARDENT PER UL-94V-0. COLOR: BLACK

BERGSTRIP™PRODUCED WITH HIGH TEMPERATURE LCP THERMOPLASTIC, FLAME RETARDENT PER UL-94V-0. COLOR: BLACK

1 |

PART NUMBERS WITH "H" AND WITHOUT SUFFIX WILL WITHSTAND EXPOSURE TO 260° C PEAK TEMPERATURE FOR 20 SECONDS IN WAVE SOLDER, INFRA-RED OR VAPOR PHASE SOLDER PROCESS.

form: A3

D

2

112

