



CHERRY G84-4400

Need a pointing device but space restrictions prevent you from using an extra mouse? The ultra-flat compact keyboard with built-in trackball is the perfect solution. The keyboard is optimally suited for 19-inch applications, slim-line PCs and laptops.



HIGHLIGHTS

- Individual keys with Gold Crosspoint contacts (ML technology)
- Designed for continuous usage - over 20 mill. confirmations per key
- High level of reliability and unique precision confirmation feeling
- Minimal space requirements
- Lightweight
- Can also be delivered without 'Windows® keys' (83 keys)
- Complete functions of a standard keyboard
- Can be used with the standard drivers of the operating system
- Ideal for 19" applications and mobile use

SCOPE OF DELIVERY

- Manual
- Keyboard

TECHNICAL DATA

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no

SWITCHES: CHERRY ML1A-11XX KS ML

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black
Actuation force	45 cN

Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

PRODUCT VARIANTS

PART NUMBER	LAYOUT	COLOUR	SWITCHES
G84-4400LPBBE-2	BE (Belgium)	black	CHERRY ML
G84-4400	CH (Switzerland)	black	CHERRY ML
G84-4400LPBDE-2	DE (Germany)	black	CHERRY ML
G84-4400LPBEU-2	EU (USA+ €- Symbol)	black	CHERRY ML
G84-4400LPBFR-2	FR (France)	black	CHERRY ML
G84-4400LPBGB-2	GB (United Kingdom)	black	CHERRY ML
G84-4420LPBEU-2	US (USA)	black	CHERRY ML
G84-4400LUBBE-2	BE (Belgium)	black	CHERRY ML
G84-4400	CH (Switzerland)	black	CHERRY ML
G84-4400LUBDE-2	DE (Germany)	black	CHERRY ML
G84-4400LUBEU-2	EU (USA+ €- Symbol)	black	CHERRY ML
G84-4400LUBFR-2	FR (France)	black	CHERRY ML
G84-4400LUBGB-2	GB (United Kingdom)	black	CHERRY ML
G84-4400LUBIT-2	IT (Italy)	black	CHERRY ML
G84-4400LUBPN-2	PN (PanNordic)	black	CHERRY ML
G84-4400LUBTQ-2	TQ (Turkey)	black	CHERRY ML
G84-4420LUBEU-2	US (USA)	black	CHERRY ML
G84-4400	CH (Switzerland)	light-grey	CHERRY ML
G84-4400LPBDE-0	DE (Germany)	light-grey	CHERRY ML
G84-4400LPBEU-0	EU (USA+ €- Symbol)	light-grey	CHERRY ML

PART NUMBER	LAYOUT	COLOUR	SWITCHES
G84-4400LPBFR-0	FR (France)	light-grey	CHERRY ML
G84-4400LPBGB-0	GB (United Kingdom)	light-grey	CHERRY ML
G84-4400LPBRB-0	RB (US / Cyrillic)	light-grey	CHERRY ML
G84-4420LPBEU-0	US (USA)	light-grey	CHERRY ML
G84-4400LUBBE-0	BE (Belgium)	light-grey	CHERRY ML
G84-4400	CH (Switzerland)	light-grey	CHERRY ML
G84-4400LUBDE-0	DE (Germany)	light-grey	CHERRY ML
G84-4400LUBEU-0	EU (USA+ €-Symbol)	light-grey	CHERRY ML
G84-4400LUBFR-0	FR (France)	light-grey	CHERRY ML
G84-4400LUBGB-0	GB (United Kingdom)	light-grey	CHERRY ML
G84-4400	IT (Italy)	light-grey	CHERRY ML
G84-4400	TQ (Turkey)	light-grey	CHERRY ML
G84-4420LUBEU-0	US (USA)	light-grey	CHERRY ML

G84-4400 [G84-4400LPBBE-2]



Layout: BE (Belgium)
Product colour: Black
Switches: CHERRY ML

Part number	G84-4400LPBBE-2
EAN	4025112062643

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE

Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11

System Requirements-Hardware	PS/2
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black

Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

CHERRY G84-4400 [G84-4400]



Layout: CH (Switzerland)

Product colour: Black

Switches: CHERRY ML

Part number	G84-4400
-------------	----------

PRODUCT INFORMATION

Model number	ML4400
--------------	--------

Reliability	MTBF 90: > 10 Mio.
-------------	--------------------

Warranty	2 years warranty
----------	------------------

Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
-------------------	---

Software support	CHERRY KEYS
------------------	-------------

Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
------------------	--

System Requirements-Hardware	PS/2
------------------------------	------

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact [75%]
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN

Initial force 30 cN

Final force 85 cN

G84-4400 [G84-4400LPBDE-2]



Layout: DE (Germany)

Product colour: Black

Switches: CHERRY ML

Part number	G84-4400LPBDE-2
EAN	4025112062667

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
System Requirements-Hardware	PS/2
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black

Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LPBEU-2]



Layout: EU (USA+ €-Symbol)

Product colour: Black

Switches: CHERRY ML

Part number	G84-4400LPBEU-2
-------------	-----------------

EAN	4025112062698
-----	---------------

UPC	840183601119
-----	--------------

PRODUCT INFORMATION

Model number	ML4400
--------------	--------

Reliability	MTBF 90: > 10 Mio.
-------------	--------------------

Warranty	2 years warranty
----------	------------------

Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
-------------------	---

Software support	CHERRY KEYS
------------------	-------------

Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
------------------	--

System Requirements-Hardware	PS/2
------------------------------	------

Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g
---------------------------	---------------------------------

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	83
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact [75%]
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no

Spring	Stainless steel
Cover colour	black
Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LPBFR-2]



Layout: FR (France)
Product colour: Black
Switches: CHERRY ML

Part number	G84-4400LPBFR-2
EAN	4025112062704

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE

Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11

System Requirements-Hardware	PS/2
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black

Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LPBGB-2]



Layout: GB (United Kingdom)

Product colour: Black

Switches: CHERRY ML

Part number	G84-4400LPBGB-2
EAN	4025112062711

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
System Requirements-Hardware	PS/2
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black

Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4420LPBEU-2]



Layout: US (USA)

Product colour: Black

Switches: CHERRY ML

Part number	G84-4420LPBEU-2
EAN	4025112067174
UPC	840183601195

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- China RoHS- UKCA- cURus- VDE- CE- BSMI- FCC- ICES-003 (Canada)
Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
System Requirements-Hardware	PS/2
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 659 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	83
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black

Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LUBBE-2]



Layout: BE (Belgium)
Product colour: Black
Switches: CHERRY ML

Part number	G84-4400LUBBE-2
EAN	4025112062841

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE

Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11

System Requirements-Hardware	USB-A
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black

Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

CHERRY G84-4400 [G84-4400]



Layout: CH (Switzerland)

Product colour: Black

Switches: CHERRY ML

Part number	G84-4400
-------------	----------

PRODUCT INFORMATION

Model number	ML4400
--------------	--------

Reliability	MTBF 90: > 10 Mio.
-------------	--------------------

Warranty	2 years warranty
----------	------------------

Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
-------------------	---

Software support	CHERRY KEYS
------------------	-------------

Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
------------------	--

System Requirements-Hardware	USB-A
------------------------------	-------

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN

Initial force 30 cN

Final force 85 cN

G84-4400 [G84-4400LUBDE-2]



Layout: DE (Germany)

Product colour: Black

Switches: CHERRY ML

Part number	G84-4400LUBDE-2
-------------	-----------------

EAN	4025112062865
-----	---------------

UPC	840183601126
-----	--------------

PRODUCT INFORMATION

Model number	ML4400
--------------	--------

Reliability	MTBF 90: > 10 Mio.
-------------	--------------------

Warranty	2 years warranty
----------	------------------

Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
-------------------	---

Software support	CHERRY KEYS
------------------	-------------

Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
------------------	--

System Requirements-Hardware	USB-A
------------------------------	-------

Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g
---------------------------	---------------------------------

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact [75%]
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel

Cover colour	black
Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LUBEU-2]



Layout: EU (USA+ €-Symbol)

Product colour: Black

Switches: CHERRY ML

Part number	G84-4400LUBEU-2
EAN	4025112062896
UPC	840183601140

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
System Requirements-Hardware	USB-A
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	83
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact [75%]
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel

Cover colour	black
Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LUBFR-2]



Layout: FR (France)
Product colour: Black
Switches: CHERRY ML

Part number	G84-4400LUBFR-2
EAN	4025112062902

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE

Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11

System Requirements-Hardware	USB-A
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black

Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LUBGB-2]



Layout: GB (United Kingdom)

Product colour: Black

Switches: CHERRY ML

Part number	G84-4400LUBGB-2
EAN	4025112062919
UPC	840183601157

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
System Requirements-Hardware	USB-A
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact [75%]
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel

Cover colour	black
Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LUBIT-2]



Layout: IT (Italy)

Product colour: Black

Switches: CHERRY ML

Part number	G84-4400LUBIT-2
-------------	-----------------

EAN	4025112062926
-----	---------------

PRODUCT INFORMATION

Model number	ML4400
--------------	--------

Reliability	MTBF 90: > 10 Mio.
-------------	--------------------

Warranty	2 years warranty
----------	------------------

Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
-------------------	---

Software support	CHERRY KEYS
------------------	-------------

Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
------------------	--

System Requirements-Hardware	USB-A
------------------------------	-------

Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g
---------------------------	---------------------------------

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black

Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LUBPN-2]



Layout: PN (PanNordic)

Product colour: Black

Switches: CHERRY ML

Part number	G84-4400LUBPN-2
-------------	-----------------

EAN	4025112084423
-----	---------------

PRODUCT INFORMATION

Model number	ML4400
--------------	--------

Reliability	MTBF 90: > 10 Mio.
-------------	--------------------

Warranty	2 years warranty
----------	------------------

Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
-------------------	---

Software support	CHERRY KEYS
------------------	-------------

Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
------------------	--

System Requirements-Hardware	USB-A
------------------------------	-------

Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g
---------------------------	---------------------------------

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black

Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LUBTQ-2]



Layout: TQ (Turkey)
Product colour: Black
Switches: CHERRY ML

Part number	G84-4400LUBTQ-2
EAN	4025112075926

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE

Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11

System Requirements-Hardware	USB-A
------------------------------	-------

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN

Initial force 30 cN

Final force 85 cN

G84-4400 [G84-4420LUBEU-2]



Layout: US (USA)

Product colour: Black

Switches: CHERRY ML

Part number	G84-4420LUBEU-2
-------------	-----------------

EAN	4025112067921
-----	---------------

UPC	840183601218
-----	--------------

PRODUCT INFORMATION

Model number	ML4400
--------------	--------

Reliability	MTBF 90: > 10 Mio.
-------------	--------------------

Warranty	2 years warranty
----------	------------------

Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
-------------------	---

Software support	CHERRY KEYS
------------------	-------------

Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
------------------	--

System Requirements-Hardware	USB-A
------------------------------	-------

Dimensions inc. packaging	385 mm × 195 mm × 30 mm 659 g
---------------------------	---------------------------------

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	83
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact [75%]
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel

Cover colour	black
Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

CHERRY G84-4400 [G84-4400]



Layout: CH (Switzerland)

Product colour: White

Switches: CHERRY ML

Part number	G84-4400
-------------	----------

PRODUCT INFORMATION

Model number	ML4400
--------------	--------

Reliability	MTBF 90: > 10 Mio.
-------------	--------------------

Warranty	2 years warranty
----------	------------------

Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
-------------------	---

Software support	CHERRY KEYS
------------------	-------------

Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
------------------	--

System Requirements-Hardware	PS/2
------------------------------	------

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact [75%]
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN

Initial force 30 cN

Final force 85 cN

G84-4400 [G84-4400LPBDE-0]



Layout: DE (Germany)

Product colour: White

Switches: CHERRY ML

Part number	G84-4400LPBDE-0
EAN	4025112026386

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
System Requirements-Hardware	PS/2
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black

Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LPBEU-0]



Layout: EU (USA+ €-Symbol)

Product colour: White

Switches: CHERRY ML

Part number	G84-4400LPBEU-0
-------------	-----------------

EAN	4025112026362
-----	---------------

UPC	840183601102
-----	--------------

PRODUCT INFORMATION

Model number	ML4400
--------------	--------

Reliability	MTBF 90: > 10 Mio.
-------------	--------------------

Warranty	2 years warranty
----------	------------------

Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
-------------------	---

Software support	CHERRY KEYS
------------------	-------------

Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
------------------	--

System Requirements-Hardware	PS/2
------------------------------	------

Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g
---------------------------	---------------------------------

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	83
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact [75%]
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no

Spring	Stainless steel
Cover colour	black
Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LPBFR-0]



Layout: FR (France)
Product colour: White
Switches: CHERRY ML

Part number	G84-4400LPBFR-0
EAN	4025112026867

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE

Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11

System Requirements-Hardware	PS/2
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black

Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LPBGB-0]



Layout: GB (United Kingdom)

Product colour: White

Switches: CHERRY ML

Part number	G84-4400LPBGB-0
-------------	-----------------

EAN	4025112026850
-----	---------------

PRODUCT INFORMATION

Model number	ML4400
--------------	--------

Reliability	MTBF 90: > 10 Mio.
-------------	--------------------

Warranty	2 years warranty
----------	------------------

Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
-------------------	---

Software support	CHERRY KEYS
------------------	-------------

Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
------------------	--

System Requirements-Hardware	PS/2
------------------------------	------

Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g
---------------------------	---------------------------------

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black

Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LPBRB-0]



Layout: RB (US / Cyrillic)

Product colour: White

Switches: CHERRY ML

Part number	G84-4400LPBRB-0
-------------	-----------------

EAN	4025112037856
-----	---------------

PRODUCT INFORMATION

Model number	ML4400
--------------	--------

Reliability	MTBF 90: > 10 Mio.
-------------	--------------------

Warranty	2 years warranty
----------	------------------

Product approvals	<ul style="list-style-type: none">- China RoHS- UKCA- cURus- VDE- CE- BSMI- ICES-003 (Canada)- FCC
-------------------	---

Software support	CHERRY KEYS
------------------	-------------

Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
------------------	--

System Requirements-Hardware	PS/2
------------------------------	------

Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g
---------------------------	---------------------------------

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	83
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black
Actuation force	45 cN

Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4420LPBEU-0]



Layout: US (USA)

Product colour: White

Switches: CHERRY ML

Part number	G84-4420LPBEU-0
EAN	4025112067167
UPC	840183601188

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- China RoHS- UKCA- cURus- VDE- CE- BSMI- FCC- ICES-003 (Canada)
Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
System Requirements-Hardware	PS/2
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 659 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	83
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	without Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black

Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LUBBE-0]



Layout: BE (Belgium)

Product colour: Grey

Switches: CHERRY ML

Part number	G84-4400LUBBE-0
EAN	4025112049330

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
System Requirements-Hardware	USB-A
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	with Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black

Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

CHERRY G84-4400 [G84-4400]



Layout: CH (Switzerland)

Product colour: Grey

Switches: CHERRY ML

Part number	G84-4400
-------------	----------

PRODUCT INFORMATION

Model number	ML4400
--------------	--------

Reliability	MTBF 90: > 10 Mio.
-------------	--------------------

Warranty	2 years warranty
----------	------------------

Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
-------------------	---

Software support	CHERRY KEYS
------------------	-------------

Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
------------------	--

System Requirements-Hardware	USB-A
------------------------------	-------

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	with Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black
Actuation force	45 cN

Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LUBDE-0]



Layout: DE (Germany)

Product colour: Grey

Switches: CHERRY ML

Part number	G84-4400LUBDE-0
EAN	4025112026881

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
System Requirements-Hardware	USB-A
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	with Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black

Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LUBEU-0]



Layout: EU (USA+ €-Symbol)

Product colour: Grey

Switches: CHERRY ML

Part number	G84-4400LUBEU-0
EAN	4025112037849
UPC	840183601133

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
System Requirements-Hardware	USB-A
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	83
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact [75%]
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	with Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no

Spring	Stainless steel
Cover colour	black
Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LUBFR-0]



Layout: FR (France)
Product colour: Grey
Switches: CHERRY ML

Part number	G84-4400LUBFR-0
EAN	4025112026904

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
System Requirements-Hardware	USB-A
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	with Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black

Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4400LUBGB-0]



Layout: GB (United Kingdom)

Product colour: Grey

Switches: CHERRY ML

Part number	G84-4400LUBGB-0
EAN	4025112026898

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
System Requirements-Hardware	USB-A
Dimensions inc. packaging	385 mm × 195 mm × 30 mm 668 g

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	40 °C
----------------------------	-------

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	with Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black

Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

CHERRY G84-4400 [G84-4400]



Layout: IT (Italy)
Product colour: Grey
Switches: CHERRY ML

Part number	G84-4400
-------------	----------

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE

Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11

System Requirements-Hardware	USB-A
------------------------------	-------

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	with Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black
Actuation force	45 cN

Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

CHERRY G84-4400 [G84-4400]



Layout: TQ (Turkey)
Product colour: Grey
Switches: CHERRY ML

Part number	G84-4400
-------------	----------

PRODUCT INFORMATION

Model number	ML4400
Reliability	MTBF 90: > 10 Mio.
Warranty	2 years warranty
Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE

Software support	CHERRY KEYS
Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11

System Requirements-Hardware	USB-A
------------------------------	-------

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	84
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	with Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no
Spring	Stainless steel
Cover colour	black
Bottom housing colour	black
Actuation force	45 cN

Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

G84-4400 [G84-4420LUBEU-0]



Layout: US (USA)

Product colour: Grey

Switches: CHERRY ML

Part number	G84-4420LUBEU-0
-------------	-----------------

EAN	4025112067914
-----	---------------

UPC	840183601201
-----	--------------

PRODUCT INFORMATION

Model number	ML4400
--------------	--------

Reliability	MTBF 90: > 10 Mio.
-------------	--------------------

Warranty	2 years warranty
----------	------------------

Product approvals	<ul style="list-style-type: none">- BSMI- RCM- CE- cURus- FCC- ICES-003 (Canada)- UKCA- VCCI- VDE
-------------------	---

Software support	CHERRY KEYS
------------------	-------------

Operating system	<ul style="list-style-type: none">- Windows Vista or higher- Windows XP- Windows 7- Windows 8- Windows 10- Windows 11
------------------	--

System Requirements-Hardware	USB-A
------------------------------	-------

Dimensions inc. packaging	385 mm × 195 mm × 30 mm 659 g
---------------------------	---------------------------------

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

CABLE

Cable length	175 cm
--------------	--------

KEYBOARD

Keycap material	ABS
Key labeling	Laser etching
Palm rest	Palm rest not available
USB-Hub	no
Number of keys	83
Illumination	no
Status LEDs	in housing
Key technology	Mechanical
Service life per key (in million strokes)	20 mio. actuations
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact [75%]
N-Key Rollover	no
Anti-ghosting	no
Key encryption	no
Windows key	with Windows key

SWITCHES: ML1A-11JW

Type	mechanical, MX
Operating life	>20m.
stem colour	black
Pre-Travel	1.500 mm
RGB	no

Spring	Stainless steel
Cover colour	black
Bottom housing colour	black
Actuation force	45 cN
Actuation point force	50 cN
Initial force	30 cN
Final force	85 cN

© Cherry Europe GmbH

Cherrystraße 2 · 91275 Auerbach/OPf. · Germany
cherry-world.com · cherry.de

Sales Support · Technischer Support · eHealth Support

+49 9643 - 2061 - 100
www.cherry.de/de-de/kontakt

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products. Properties are not guaranteed.