

Nanonics

TE Internal #: 1-1589483-5

Receptacle, Wire-to-Board, 25 Position, .64 mm [.025 in] Centerline, Printed Circuit Board, Power, Microminiature & Nanominiature D


Connectors

View on TE.com >



Connectors > D-Shaped Connectors > Microminiature & Nanominiature D Connectors >

DUALOBE Receptacle Connector: Plastic Shell, 2 Row Config



Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 25

Centerline (Pitch): .64 mm [.025 in]

Termination Method to Wire & Cable

Mechanical Attachment

Connector Mounting Type

Sealable: No

All DUALOBE Receptacle Connector: Plastic Shell, 2 Row Config (20)

Features

Product Type Features

Receptacle
Wire-to-Board
No
Printed Circuit Board
25
Socket
Installed
1 A
Surface Mount

Preterminated Flying Leads

Board Mount



Housing Features

Centerline (Pitch)	.64 mm[.025 in]
Usage Conditions	
Operating Temperature Range	-200 - 200 °C[-328 - 392 °F]
Operation/Application	
Circuit Application	Power

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Pb (40% in 74023047) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts








Customers Also Bought





















Documents

Product Drawings
STL025L2AN = SMT CONN

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1589483-5_U.2d_dxf.zip

Receptacle, Wire-to-Board, 25 Position, .64 mm [.025 in] Centerline, Printed Circuit Board, Power, Microminiature & Nanominiature D Connectors



English

Customer View Model

ENG_CVM_CVM_1-1589483-5_U.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1589483-5_U.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

1589483 Nanonics Cross Reference

English