

Part Number: 5025780600

Product Description: CLIK-Mate Plug Housing, 1.50mm Pitch, Single Row, Positive Lock, 6

Circuits, Natural

Series Number: 502578

Status: Active

Product Category: Connector Housings



Documents & Resources

Drawings

Drawing 5025780600_sd.pdf

3D Models and Design Files

3D Model PDF 5025780600.pdf 3D Model 5025780600_stp.zip

Specifications

Application Specification AS-502578-001-001.pdf
Application Specification AS-503395-001-001.pdf
Packaging Specification SPK-502578-001-001.pdf
Product Specification 5025780000-PS-000.pdf
Product Specification 5025780002-PS-000.pdf
Product Specification 5025780003-PS-000.pdf
Product Specification 5025781000-PS-000.pdf
Product Specification 5025781000-PS-CHI-000.pdf
Product Specification 5025781000-PS-JAP-000.pdf
Product Specification 5025781002-PS-000.pdf
Product Specification 5025781003-PS-000.pdf
Product Specification 5025781003-PS-000.pdf
Product Specification 5025781003-PS-000.pdf
Product Specification 5025781003-PS-000.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	©
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21

REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Connector Housings
Series	502578
Description	CLIK-Mate Plug Housing, 1.50mm Pitch, Single Row, Positive Lock, 6 Circuits, Natural
Application	Signal, Wire-to-Board
Product Family	CLIK-Mate Wire-to-Board Connectors
Product Name	CLIK-Mate
UPC	800756700229

Agency

UL	E29179

Physical

Circuits (maximum)	6
Color - Resin	Natural
Flammability	SC-0
Gender	Plug

Glow-Wire Capable	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	PBT
Net Weight	334.300/mg
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	1.50mm
Pitch - Termination Interface	1.50mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40° to +105°C

Mates With / Use With

Mates with Part(s)

Description	Part Number
1.50mm Pitch CLIK-Mate Bottom Entry Single Row PCB Receptacles	503395
1.50mm Pitch CLIK-Mate Right- Angle Single Row PCB Receptacles	<u>213226</u>
1.50mm Pitch CLIK-Mate Right- Angle Single Row PCB Receptacles	502585
1.50mm Pitch CLIK-Mate Right- Angle Single Row PCB Receptacles	<u>503175</u>
1.50mm Pitch CLIK-Mate Vertical Single Row PCB Receptacles	<u>213225</u>
1.50mm Pitch CLIK-Mate Vertical Single Row PCB Receptacles	502584
1.50mm Pitch CLIK-Mate Vertical Single Row PCB Receptacles	<u>503159</u>

Use with Part(s)

Description	Part Number
Pre-Crimped Lead CLIK-Mate 1.50mm Male-to-CLIK-Mate 1.50mm Male, Tin (Sn) Plating, 300.00mm Length, 24 AWG, Black	/content/molex/molex-dot- com/us/en/products/product- page.html/797581011.html

1.50mm Pitch CLIK-Mate Male Crimp Terminals	502579
1.50mm Pitch CLIK-Mate Male Crimp Terminals	503429
CLIK-Mate 1.50mm Pitch Male Crimp Terminals	213028
CLIK-Mate 1.50mm Pitch Male Crimp Terminals	213029
Pre-Crimped Lead Clik-Mate Male- to-Clik-Mate Male	<u>215710</u>
Pre-Crimped Lead Clik-Mate Male- to-Pigtail	215711

This document was generated on Aug 07, 2023