



 PRODUCT-DETAILS

OT315KAUC6AZ

OT315KAUC6AZ Safety switch



General Information

| | |
|-----------------------|----------------------------|
| Extended Product Type | OT315KAUC6AZ |
| Product ID | 1SCA022542R6480 |
| EAN | 6417019171265 |
| Catalog Description | OT315KAUC6AZ Safety switch |

| | |
|------------------|---|
| Long Description | <p>Safety switch, 6-p. 415V AC23 315A, 160kW. Mounted auxiliary contact: 4NO2NC. Steel sheet enclosure. IP65. RedYellow Pistol handle. Interlocked cover. Defeatable interlocking.</p> <p>The enclosed switch is using a galvanised steel enclosure, with polyester coating. It is suitable for outdoor use with respect to UV light and ingress protection. The enclosure have inbuilt gas pressure relief function to protect the user in case of an internal arc. The door is earthed via the hinges. The enclosure is prepared for single and parallel cables. Cable entry types can be blank , ring-flange or C-flange type (FL21), with different cable configuration, like top/bottom or bottom/bottom. The handle is padlockable for 3 padlocks, cover is interlocked, and interlock function can be bypassed for thermography.</p> |
|------------------|---|

Material Compliance

| | |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 1SCC340076D0201 |
| RoHS Declaration | 1SCC340075D0201 |
| RoHS Information | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Toxic Substances Control
Act - TSCA

1SCC340095D0201

Popular Downloads

| | |
|-----------------------------------|---------------------|
| Data Sheet, Technical Information | 1SCC340015C0201 |
| Instructions and Manuals | 1SCC340016M0005 |
| Mechanical Drawings | OTKM808023PBL4C.stp |

Environmental

| | |
|----------------------|------------------------|
| Degree of Protection | acc. to IEC 60529 IP65 |
| Pollution Degree | 3 |

Ordering

| | |
|--------------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85363090 |
| Country or Territory of Origin | Finland |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 800 mm |
| Product Net Height | 800 mm |
| Product Net Depth / Length | 230 mm |
| Product Net Weight | 41.14 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 815 mm |
| Package Level 1 Depth / Length | 910 mm |
| Package Level 1 Height | 325 mm |
| Package Level 1 Gross Weight | 45 kg |
| Package Level 1 EAN | 6417019171265 |

Technical

| | |
|--|---|
| Cable Entry Position | Bottom/Bottom |
| Cable Outlets Per Side | Blank / 4xC-flange, Knock-outs: 2x10mm, 12.5mm, 20.5mm, 25.5mm, 32.5mm |
| Color | RAL7032 |
| Connecting Capacity Main Circuit | Hole Diameter 10 mm Screw Clamp / PE Terminal 8pc,25 ... 120 mm ² |
| Conventional Thermal Current (I_{the}) | Fully Enclosed 315 A |
| Degree of Protection | acc. to IEC 60529 IP65 |
| Enclosure Material | Steel sheet |
| Handle Color | Red / Yellow |
| Handle Type | Pistol handle |
| Impact Resistance Rating | Housing IK09 |
| Maximum Mounted | 4 NO, 2 NC |

| | |
|---|--|
| Auxiliary Contacts | |
| Mounted Auxiliary Contacts | 4 NO, 2 NC |
| Neutral Type | No Neutral Terminal |
| Number of Auxiliary Contacts NC | 2 |
| Number of Auxiliary Contacts NO | 4 |
| Number of Poles | 6P |
| Pollution Degree | 3 |
| Power Loss | at Rated Operating Conditions per Pole 6.5 W |
| Rated Conditional Short-Circuit Current (I_{nc}) | 61.5 kA |
| Rated Insulation Voltage (U_i) | 750 V |
| Rated Operational Current AC-22A (I_e) | (380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A |
| Rated Operational Current AC-23A (I_e) | (380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A |
| Rated Operational Power AC-23A (P_e) | (380 ... 415 V) 160 kW (500 V) 200 kW (690 V) 250 kW |
| Rated Operational Voltage | Main Circuit 1000 V |
| Rated Short-Circuit Making Capacity (I_{cm}) | (1000 V AC) 65 kA |
| Rated Short-time Withstand Current Low Voltage (I_{cw}) | for 1 s 15 kA |
| Recommended Screw Driver | Main Circuit M10 |
| Standards | IEC 60947-1, -3 |
| Tightening Torque | Main Circuit 44 N·m |

Technical UL/CSA

| | |
|--------------------------|----------------------------|
| Recommended Screw Driver | Main Circuit M10 |
| Tightening Torque | Main Circuit 44 N·m |

Certificates and Declarations

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SCC340025D2704 |
|--------------------------------|-----------------|

External Classifications and Standards

| | |
|------------------------------------|--|
| Object Classification Code | Q |
| ETIM 9 | EC000216 - Switch disconnecter (low voltage) |
| ETIM 10 | EC000216 - Switch disconnecter (AC) |
| UNSPSC | 39122205 |
| IDEA Granular Category Code (IGCC) | 5166 >> Safety switch |
| eClass | V11.1 : 27371403 |
| WEEE Category | 4. Large Equipment (Any External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

