

## Touch panel - TP 3156W/P - 2403462

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 39.6 cm/15.6" TFT-display (Projective-capacitive (PCAP)), 1366 x 768 pixel(s) (WXGA), 65536 colors, Arm® Cortex®-A8, 1000 MHz, 2x USB host 2.0, 1 x Ethernet (10/100 Mbps), RJ45, Windows® Embedded Compact 7 and user software: Visu+. (bus system: without)


Similar figure

### Your advantages

- ✓ Robust and sturdy, thanks to glass front suitable for industrial use
- ✓ Fast response and display refresh, thanks to powerful processor
- ✓ Flexible connection to third-party systems by means of various drivers
- ✓ Integrated Visu+ visualization software
- ✓ Mobile system access with the Visu+ mobile app



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 363561
GTIN	4055626363561
Weight per Piece (excluding packing)	4,000.000 g
Custom tariff number	84714100
Country of origin	Germany

### Technical data

#### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

#### Dimensions

Outer dimensions: width, height, depth	436 mm x 278 mm x 6 mm (Dimensions of the front plate)
Installation dimensions: width, height, depth	425 mm x 260 mm x 53 mm (Installation cutout)

#### Display

Display	39.6 cm/15.6" TFT
---------	-------------------

# Touch panel - TP 3156W/P - 2403462

## Technical data

### Display

Screen resolution	1366 x 768 Pixel(s) (WXGA)
Touch technology	Projective-capacitive (PCAP)
Brightness	320 cd/m <sup>2</sup> typical (adjustable)
Backlighting	LED
Display backlight MTBF	70000 h
Colors	65536 colors
Reading angle left	80 °
Reading angle right	80 °
Reading angle top	80 °
Reading angle bottom	80 °

### Computer data

Processor	Arm <sup>®</sup> Cortex <sup>®</sup> -A8, 1000 MHz
Operating system	Windows <sup>®</sup> Embedded Compact 7
User software	Visu+
RAM	512 MB LPDDR RAM
Mass storage	NAND-Flash, 1 GB
Network	1 x Ethernet (10/100 Mbps), RJ45
Interfaces	2x USB Host 2.0
Bus system	without
Slots	1x SD
Realtime clock	Yes (battery-backed)
Service life of battery	5 years (typical)

### General

Material front plate	Aluminum (natural anodized)
Housing material	Steel sheet, zinc-plated
Mounting type	Front installation
Weight	4000 g

### Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
	NEMA 4X
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	20 % ... 85 % (non-condensing)
Permissible humidity (storage/transport)	20 % ... 85 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

### Device supply

Supply voltage	24 V DC
Supply voltage range	18 V DC ... 30 V DC

# Touch panel - TP 3156W/P - 2403462

## Technical data

### Device supply

Typical current consumption	1 A
Power consumption	typ. 24 W
Power supply unit	24 V DC $\pm 20\%$

### Standards and Regulations

Shock	DIN EN 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

### Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 15;
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Classifications

### eCl@ss

eCl@ss 4.0	27330200
eCl@ss 4.1	27330200
eCl@ss 5.0	27330200
eCl@ss 5.1	27330200
eCl@ss 6.0	27242300
eCl@ss 7.0	27242302
eCl@ss 8.0	27242302
eCl@ss 9.0	27330201

### ETIM

ETIM 4.0	EC001412
ETIM 5.0	EC001412
ETIM 6.0	EC001412
ETIM 7.0	EC001412

### UNSPSC

UNSPSC 13.2	43211904
UNSPSC 18.0	43211904
UNSPSC 19.0	43211904
UNSPSC 20.0	43211904
UNSPSC 21.0	43211904

## Approvals

### Approvals

## Touch panel - TP 3156W/P - 2403462

### Approvals

#### Approvals

UL Listed / cUL Listed / cULus Listed

---

#### Ex Approvals

UL Listed / cUL Listed / cULus Listed

---

### Approval details

UL Listed



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

FILE E 205795

cUL Listed



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

FILE E 205795

cULus Listed



### Accessories

#### Accessories

##### Battery module

Battery / accumulator - HMI BATTERY - 2701383

Lithium battery



#### Mounting material

Mounting material - HMI SCB MOUNTING KIT 4 - 2701384



HMI mounting kit for installation on a front plate. The mounting kit includes 4 x mounting brackets, 4 x screw threads, and a hexagonal wrench.

## Touch panel - TP 3156W/P - 2403462

### Accessories

#### Mounting material - HMI SCB MOUNTING KIT 6 - 2701385



HMI mounting kit for installation on a front plate. The mounting kit includes 6 x mounting brackets, 6 x screw threads, and a hexagonal wrench.

---

#### Mounting material - HMI SCB MOUNTING KIT 8 - 2701387



HMI mounting kit for installation on a front plate. The mounting kit includes 8 x mounting brackets, 8 x screw threads, and a hexagonal wrench.

---

#### Mounting material - HMI WALL MOUNTING KIT - 2701380



HMI mounting kit for panel installation. The mounting kit includes 2 spring clips.

---

### Parameterization memory

#### Program / configuration memory - SD FLASH 2GB - 2988162



Program and configuration memory, for extending the internal flash memory, pluggable, 2 GB.

---

### PCB plug

#### Printed-circuit board connector - MC 1,5/ 3-STF-3,5 BD:1-3 - 1751312



PCB connector, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm<sup>2</sup>, number of positions: 3, pitch: 3.5 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Tin

---

### Storage medium

## Touch panel - TP 3156W/P - 2403462

### Accessories

USB memory stick - USB FLASH DRIVE - 2402809



USB memory stick, 8 GB