

3M™ Double Coated Tape GTM715Plus, Clear, 1200 mm x 50 m, 1 Roll/Case

UPC #: 06912504317727, 3M Stock #: 7100315488, Legacy 3M Stock #: XP003813142, Your Catalogue #: [Manage](#)



[View Images](#)

Details

Adhesive Type	Acrylic	Product Color	Transparent
Backing (Carrier) Material	PET	Shelf Life	730 Days
Brand	3M™	Smallest Saleable Unit*	Roll
Overall Length (Metric)	50.0 Meter	Total Tape Thickness without Liner (metric)	0.15 mm
Overall Width (Metric)	1200 mm		

Details

- General purpose Double coated PET tape
- Good bonding performance with good initial tack
- High peel strength even at high Temperature
- High dynamic shear

3M™ Double Coated PET Tape GTM715 with high adhesion to a variety of surfaces, including metal, high/middle surface energy substrates for general bonding purpose in wide applications such as Foam Bonding, PFC Bonding and Lens Bonding

Elongation at Break	2.25
Indoor/Outdoor	Both
Maximum Operating Temperature (Celsius)	90 °C
Minimum Operating Temperature (Celsius)	0 °C
Number of Adhesive Sides	Single-sided
Product Color	Gray
Product Type	Stress Control
Suitable for High Voltage	No
Total Tape Thickness without Liner (Imperial)	30 mil
Total Tape Thickness without Liner (Metric)	0.76 mm
UV Resistant	No