



CL2000 locks are ideal for a wide range of light duty entry control applications. Fully programmable on the door via the keypad with a multiple range of functions making them particularly suitable for use in health, education, commercial and residential environments.

## Technical Specifications

Functions:	3 available
Operations:	80,000
Batteries:	2 x 1.5 v AA Cells
Low Battery Warning:	Red LED will flash on opening to indicate batteries need to be changed
Memory:	Stores 80 different User Codes
Battery Override:	Lock can be opened by attaching a PP3 battery to contact points and entering the Master code
Spindle type:	Flat bar spindle, 8mm adaptor supplied
Material:	Zinc Alloy
Door thickness:	35mm - 65mm (13/8" - 2 1/2")
Buttons:	Individual stainless steel buttons
Non handed:	Locks will fit doors hung on the left or right
Fitting Options:	Vertical
Finish:	PVD (Physical Vapour Deposition) hardwearing low maintenance finishes BS (brushed steel) and PB (polished brass)
Keying alike:	Locks can be supplied as keyed alike on request
Key Override:	As standard
Codes:	Possible 1,110,000 combinations 4, 5, 6 digits long

## Functions:

Models:	2200, 2210, 2255
Tubular Motice Latch:	2255 outside knob will not turn unless valid code is entered. Spring latch will automatically lock the door when closed.
Surface Deadbolt:	2200 bolt slides on inside surface of door to lock or unlock. Bolt is moved manually by means of the outside knob after code input and freely by the inside knob at all times. A surface mounted keep is provided.
Mortice Deadbolt:	2210 bolt extends 25mm (1") beyond edge when locked.

## Code change method:

On door via key. Code free mode can be set via the keypad  
REM1 & REM2 included as standard

CL2000 range is a quick and easy retrofit with most basic mechanical digital locks, electronically upgrading the lock in minutes.

## External Dimensions:

