

# Product datasheet

Specifications



circuit breaker ComPacT NSXm F  
(36 kA at 415 VAC), 3P 3d, 25 A  
rating Micrologic 4.1 trip unit,  
EverLink connectors

C11F34V025L

EAN Code: 3606481992680

## Main

|                                                      |                                                                                                                                                                                                                                                                                                                      |
|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                                | ComPacT                                                                                                                                                                                                                                                                                                              |
| Product name                                         | ComPacT NSXm                                                                                                                                                                                                                                                                                                         |
| Device short name                                    | NSXm 63F                                                                                                                                                                                                                                                                                                             |
| Product or component type                            | Earth leakage circuit breaker                                                                                                                                                                                                                                                                                        |
| Device application                                   | Distribution                                                                                                                                                                                                                                                                                                         |
| Poles description                                    | 3P                                                                                                                                                                                                                                                                                                                   |
| Protected poles description                          | 3D                                                                                                                                                                                                                                                                                                                   |
| [In] rated current                                   | 25 A at 40 °C                                                                                                                                                                                                                                                                                                        |
| [Ue] rated operational voltage                       | 440 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                    |
| Network type                                         | AC                                                                                                                                                                                                                                                                                                                   |
| Network frequency                                    | 50/60 Hz                                                                                                                                                                                                                                                                                                             |
| Suitability for isolation                            | Yes conforming to IEC 60947-2                                                                                                                                                                                                                                                                                        |
| Utilisation category                                 | Category A                                                                                                                                                                                                                                                                                                           |
| [Icu] rated ultimate short-circuit breaking capacity | 85 kA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2<br>36 kA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2<br>35 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>15 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level                                    | F 36 kA 415 V AC                                                                                                                                                                                                                                                                                                     |
| Trip unit name                                       | MicroLogic 4.1                                                                                                                                                                                                                                                                                                       |
| Trip unit technology                                 | Electronic                                                                                                                                                                                                                                                                                                           |
| Trip unit protection functions                       | LSolR                                                                                                                                                                                                                                                                                                                |
| Control type                                         | Toggle                                                                                                                                                                                                                                                                                                               |
| Circuit breaker mounting mode                        | Fixed                                                                                                                                                                                                                                                                                                                |

## Complementary

|                                                     |                                                                                                                                                                                                                                                                                                  |
|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ui] rated insulation voltage                       | 500 V AC 50/60 Hz                                                                                                                                                                                                                                                                                |
| [Uimp] rated impulse withstand voltage              | 8 kV                                                                                                                                                                                                                                                                                             |
| [Ics] rated service short-circuit breaking capacity | 85 kA at 220...240 V AC 50/60 Hz conforming to IEC 60947-2<br>36 kA at 380...415 V AC 50/60 Hz conforming to IEC 60947-2<br>30 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability                               | 20000 cycles                                                                                                                                                                                                                                                                                     |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                                             |                                                                                                                                                                                                                                                               |
|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical durability                                       | 20000 cycles at 440 V In/2<br>10000 cycles at 440 V In<br>10000 cycles at 690 V In/2<br>5000 cycles at 690 V In                                                                                                                                               |
| Power dissipation per pole                                  | 1.5 W                                                                                                                                                                                                                                                         |
| Mounting support                                            | Backplate                                                                                                                                                                                                                                                     |
| Mounting position                                           | Horizontal and vertical<br>Flat on the back                                                                                                                                                                                                                   |
| Upside connection                                           | Front                                                                                                                                                                                                                                                         |
| Downside connection                                         | Front                                                                                                                                                                                                                                                         |
| Connection terminals                                        | 1 Everlink lug wire size 2.5...70 mm², fine stranded copper<br>1 Everlink lug wire size 2.5...95 mm², rigid or stranded aluminium/copper                                                                                                                      |
| Connection pitch                                            | 35 mm with spreaders<br>27 mm without spreaders                                                                                                                                                                                                               |
| 9 mm pitches                                                | 9 module                                                                                                                                                                                                                                                      |
| Trip unit rating                                            | 25 A at 40 °C                                                                                                                                                                                                                                                 |
| Long-time pick-up adjustment type Ir (thermal protection)   | Adjustable 9 settings                                                                                                                                                                                                                                         |
| [Ir] long-time protection pick-up adjustment range          | 10...25 A                                                                                                                                                                                                                                                     |
| Long-time protection delay adjustment type tr               | Fixed                                                                                                                                                                                                                                                         |
| [tr] long-time protection delay adjustment range            | 200 s at 1.5 x Ir<br>8 s at 6 x Ir<br>5 s at 7.2 x Ir                                                                                                                                                                                                         |
| Thermal memory                                              | 20 minutes before and after tripping                                                                                                                                                                                                                          |
| Short-time protection pick-up adjustment type Isd           | Adjustable 9 settings                                                                                                                                                                                                                                         |
| [Isd] Short-time protection pick-up adjustment range        | 1.5...10 x Ir                                                                                                                                                                                                                                                 |
| Short-time protection delay adjustment type tsd             | Fixed                                                                                                                                                                                                                                                         |
| Instantaneous protection pick-up adjustment type Ii         | Fixed                                                                                                                                                                                                                                                         |
| [Ii] instantaneous protection pick-up adjustment range      | 375 A                                                                                                                                                                                                                                                         |
| Earth-leakage protection                                    | Integrated                                                                                                                                                                                                                                                    |
| Earth-leakage protection class                              | Class A<br>Class AC                                                                                                                                                                                                                                           |
| Earth-leakage protection sensitivity adjustment type IΔn    | Adjustable                                                                                                                                                                                                                                                    |
| [IΔn] earth-leakage protection sensitivity adjustment range | 30 mA<br>100 mA<br>300 mA<br>500 mA<br>1 A<br>3 A<br>5 A                                                                                                                                                                                                      |
| Earth-leakage sensitivity                                   | 30 mA for class A<br>100 mA for class A<br>300 mA for class A<br>500 mA for class A<br>1 A for class A<br>30 mA for class AC<br>100 mA for class AC<br>300 mA for class AC<br>500 mA for class AC<br>1 A for class AC<br>3 A for class AC<br>5 A for class AC |
| Earth-leakage protection time delay adjustment type Δt      | Adjustable                                                                                                                                                                                                                                                    |

|                                                                  |                                                                                                              |
|------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| <b>[Δt] Earth-leakage protection time delay adjustment range</b> | 0 ms                                                                                                         |
|                                                                  | 60 ms                                                                                                        |
|                                                                  | 150 ms                                                                                                       |
|                                                                  | 500 ms                                                                                                       |
|                                                                  | 1000 ms                                                                                                      |
| <b>Number of slots for electrical auxiliaries</b>                | 1 slot(s) for auxiliary switch OF<br>1 slot(s) for alarm switch SD<br>1 slot(s) for voltage release MN or MX |
| <b>Local signalling</b>                                          | Flag (green) for presence of auxiliary contacts                                                              |
| <b>Width (W)</b>                                                 | 108 mm                                                                                                       |
| <b>Height (H)</b>                                                | 144 mm                                                                                                       |
| <b>Depth (D)</b>                                                 | 80 mm                                                                                                        |
| <b>Net weight</b>                                                | 1.63 kg                                                                                                      |
| <b>Colour</b>                                                    | Grey (RAL 7016)                                                                                              |

## Environment

|                                              |                                                 |
|----------------------------------------------|-------------------------------------------------|
| <b>Standards</b>                             | EN/IEC 60947-2                                  |
| <b>Overvoltage category</b>                  | IV                                              |
| <b>Electrical shock protection class</b>     | Class II on front face                          |
| <b>Pollution degree</b>                      | 3 conforming to IEC 60664-1                     |
| <b>IP degree of protection</b>               | IP40 conforming to IEC 60529                    |
| <b>IK degree of protection</b>               | IK07 conforming to IEC 62262                    |
| <b>Ambient air temperature for operation</b> | -25...70 °C                                     |
| <b>Ambient air temperature for storage</b>   | -40...85 °C                                     |
| <b>Relative humidity</b>                     | 0...95 %                                        |
| <b>Operating altitude</b>                    | 2000 m without derating<br>5000 m with derating |

## Packing Units

|                                     |           |
|-------------------------------------|-----------|
| <b>Unit Type of Package 1</b>       | PCE       |
| <b>Number of Units in Package 1</b> | 1         |
| <b>Package 1 Height</b>             | 14.000 cm |
| <b>Package 1 Width</b>              | 16.000 cm |
| <b>Package 1 Length</b>             | 19.000 cm |
| <b>Package 1 Weight</b>             | 1.729 kg  |
| <b>Unit Type of Package 2</b>       | S03       |
| <b>Number of Units in Package 2</b> | 4         |
| <b>Package 2 Height</b>             | 30.000 cm |
| <b>Package 2 Width</b>              | 30.000 cm |
| <b>Package 2 Length</b>             | 40.000 cm |
| <b>Package 2 Weight</b>             | 7.336 kg  |
| <b>Unit Type of Package 3</b>       | P12       |
| <b>Number of Units in Package 3</b> | 32        |
| <b>Package 3 Height</b>             | 45.000 cm |

|                  |            |
|------------------|------------|
| Package 3 Width  | 80.000 cm  |
| Package 3 Length | 120.000 cm |
| Package 3 Weight | 70.688 kg  |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                  |                                               |
|----------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint | 39                                            |
| Environmental Disclosure         | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                      |
|----------------------------------------|--------------------------------------|
| Packaging made with recycled cardboard | Yes                                  |
| Packaging without single use plastic   | Yes                                  |
| <a href="#">EU RoHS Directive</a>      | Compliant with Exemptions            |
| SCIP Number                            | Af3d4202-1697-430d-83ec-d7a972ac0ddb |
| REACH Regulation                       | <a href="#">REACH Declaration</a>    |
| Halogen-free status                    | Halogen free plastic parts product   |
| PVC free                               | Yes                                  |
| Silicone-free                          | No                                   |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| End of life manual availability | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| Take-back                       | No                                                                                                                                                                                                              |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Offer Marketing Illustration

Product benefits / Features

---



CompactT NSXm  
Range Accessories



Wireless  
indication auxiliary



Long terminal  
shield



Standard  
auxiliary contact



Rotary handles



Inter-phase barrier



Toggle padlocking  
device



MN undervoltage  
release



Standard MX shunt  
release

Offer Marketing Illustration

Product benefits / Features

CompacT NSXm  
Earth leakage circuit breaker



Efficiency

It features integrated earth leakage protection and standardized accessories – which means you save space, time, and effort.



Reliability

Optimized in size and featuring innovations tailored to your needs. Roto-active™ breaking technology helps to increase operation lifespan.



Connectivity


Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.



Offer Marketing Illustration

Product benefits / Features

CompacT NSXm  
Technical Features





Offer Marketing Illustration

Product benefits / Features

---



### Compact NSXm

#### Technical Benefits

- Come in one size and are optimized for small spaces.
- 3 or 4 pole versions
- Rated currents: 16 to 160A
- Thermal-magnetic protections
- Breaking capacities under 240/415 V  
16, 25, 36, 50, 70 kA
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker = ELCB)
- EverLink™ connectors for bare cables

Technical Illustration

Assembly's dimensions

