

Features

- High performance design
- Performance Level 3
- RS232 standard interface
- Robust tin plated steel shell
- UL 94V-0 insulator
- Flanges containing
 3.05 mm mounting
 holes for screw
 mounting to a panel

RS PRO 9 WAY STRAIGHT CRIMP 5A D-SUB CONNECTOR HOUSING PLUG SHELL

RS Stock No.: 0199085, 0199086



RS PRO is the own brand of RS. The RS PRO Seal of Approval is your assurance of professional quality, a guarantee that every part is rigorously tested, inspected, and audited against demanding standards. Making RS PRO the Smart Choice for our customers.



Product Description

From RS PRO a high-performance D-Subminiature connector with a bright tin plated steel shell with grounding indents for EMI and RFI shielding. Crimp terminations on the rear of this connector allow the easy connection of wires. These D-sub connectors have an RS232 standard interface. The pins of this subminiature connector are of high quality and feature flanges with pre-drilled 3.05mm diameter holes on either side for easy panel mounting. These d-sub connectors are ideal for use in for I/O (input/output) interconnections in a wide range of industrial and commercial applications.

General Specifications

| Number Of Contacts | 9 |
|------------------------------|---|
| Gender | Male |
| Body Orientation | Straight |
| Mounting Type | Panel Mount |
| D Connector | Standard D-Sub |
| D-Sub Shell Size | E |
| Termination Method | Crimp |
| Housing Material | Steel |
| Contact Material | Copper Alloy |
| Contact Plating | Gold |
| Application | Computers, monitors and scanners, Networking and communications equipment; Data processing equipment, Industrial equipment, Test and measurement instrumentation, Remote Sensors and data loggers, Portable electric generation equipment |
| Performance Level | 3 |
| Operating Temperature | -55°c to 125°c |
| Material Flammability Rating | UL94 V-0 |



Electrical Specifications

| Current Rating | 5.0A |
|---------------------------|-------------|
| Voltage Rating | 750V |
| Contact Resistance | $10m\Omega$ |
| Insulation Resistance | 5000ΜΩ |

Mechanical Specifications

| Wire Accommodation | 20-24 AWG |
|--------------------|-----------|
| | |

Protection Category

| IP Ratings | IP 40 |
|-------------|-------|
| ii italiigs | 11 40 |

Approvals

| Declarations | MFR Declaration of Conformity |
|--------------|-------------------------------|
|--------------|-------------------------------|



