

LOST WAX RELEASE

Technical Data Sheet

Product name: Lost Wax Release Creation date:08/08/2017 Version: 1.0

Replaces: 0.0

1 : General description

Release agent for lost waxes in precision foundry.

2 : Features

- Ecological
- Water soluble

3: Applications

Mould release agent for parts moulded with the lost wax procedure. The parts still can be painted, screen-printed, glued or thermo-welded.

In this last case, plastic parts should only be washed with water, after moulding, to eliminate the release agent.

4: Directions

- Shake the Aerosol during 2 min.
- Apply a uniform film.
- Allow to dry

A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

5: Typical product data (without propellant)

Base : Co-polymer of the methylpolysiloxane type.

Viscosity : 1000 cPs

Operating temperature : max 230°C

6: Packaging

Aerosol 12x500 ML



All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.