Datasheet

Product Name:	MIL-W-16878/6 28AWG
Product Discription:	MIL-W-16878/6 28AWG
Specification No.:	
Customer's Name:	

Description

Rated Voltage:	250V
Rated Temperature:	200℃
Reference Standard:	MIL-W-16878/6

Cross Section



Marking

No marking on the cable jacket

Applications

These wires are ideal for internal wiring of appliances, electronic equipment and other applications.

Revisions

Version	Description	Drawn by	Approved by	Date
0	New document issue	Danniel	Jason	19/05/2015

Construction

Conductor	**Stranded Sliver plated copper**		
Size(AWG)	28		
Construction(±0.008mm)	7/0.127		
Stranded Dia.(mm)Ref.	0.38		
Insulation Material	PTFE		
Insulation Color	ANY COLOR		
Ave Thickness(mm)	0.15		
Insulation Dia.(±0.08mm)	0.69		

Remark:

8775478 Red 8775474 Blue
8775462 Black 8775487 White
8775471 Brown

Characteristics

Test Item	Standard Value
Test Material	PTFE(ROHS)
Insulation resistance(20℃ MΩ*m	1000
Vol. Tesr(AC.V.60S) (V)	2000
Flammability Test	VW-1
Max.DC Resistance(20℃ Ω/km)	208.66(MAX)

Customer Approve

Seal & Stamp

Signature:

Date:

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.