



Notice : GPSP

Hint : 3

GUYARD SAS

22-24, rue Lucien Rouzet
Z.A. Villedieu sur Indre/Niherne
36250 NIHERNE FRANCE

**Water-repellent cowhide leather
type firefighter glove**

Major risks - Category III PPE

FEATURES :

- Water-repellent cowhide grain glove, fully lined with 69% para-aramid fleece, 31% twaron.
- Cuff in Natural cowhide crust, fitted with artery protector. Length from 365 to 400 mm depending on the size.
- Sewing para-aramid thread TEX35 48/4.

AVAILABLE SIZE:

- Size: 6 to 11.

PRECAUTIONS FOR USE:

- Wear the gloves on dry and clean hands. It is recommended to carry out a preliminary test of the gloves. Actual conditions of use may differ from EU type tests.
- Before any reuse, check that the gloves do not have no defect, hole, tear, abnormal wear.
- Expiration : 5 years from the date of manufacture indicated on the glove.

INNOCUITÉ CONFORT ET DEXTÉRITÉ :

- Dexterity level 4.
- The glove does not contain substances at levels known or suspected to have adverse effects on the hygiene or health of the user under foreseeable conditions of use.

MAINTENANCE AND STORAGE :

- No special maintenance is recommended. It is advisable to store the products in a cool, dry and ventilated place away from light.

RECOMMENDED USES :

- Protective glove for firefighters.

PACKAGING :

- In case of unpacking of the package, a copy of the instructions must be attached with the smallest packaging.
- Bag of 10 pairs.
- Boxes of 100 pairs.

EN ISO 21420 : 2020

EN 388 : 2016
+A1 2018

EN 407 : 2020

EN659 :
2003+A1 : 2008



CE 0333

3333 B



41334X



compliant

PERFORMANCE LEVELS :

EN 388 : 2016+A1/2018

- | | |
|---------------------|-----|
| • Abrasion : | 3/4 |
| • Cut (EN 388) : | 3/5 |
| • Tear : | 3/4 |
| • Perforation : | 3/4 |
| • Cut (ISO 13997) : | B/F |

EN 407 : 2020

- | | |
|------------------------------|-----|
| • Fire behavior : | 4/4 |
| • Contact heat : | 1/4 |
| • Convective heat : | 3/4 |
| • Radiant heat : | 3/4 |
| • Liquid metal drops : | 4/4 |
| • Molten metal projections : | X/4 |

EN 659 : 2003+A1 : 2008 +AC : 2009

- | | |
|----------------------------------|-----------|
| • Flame behavior : | compliant |
| • Convective heat : | compliant |
| • Radiant heat : | compliant |
| • Contact heat : | compliant |
| • Heat lining material : | compliant |
| • Heat shrinkage : | compliant |
| • Dexterity : | compliant |
| • Seam rupture : | compliant |
| • Removing gloves : | compliant |
| • Water penetration : | compliant |
| • Glove integrity : | compliant |
| • Chemical product penetration : | compliant |

END OF LIFE

- Destruction at the end of life must be controlled and comply with European requirements for traceability and respect for the environment.

EU type certificate issued in accordance with module B Regulation (EU) 2016/425
Manufacturing follow-up, in accordance with module D Regulation (EU) 2016/425

LEITAT n° : 0162
Afnor Certification n° : 0333

The EU declaration of conformity is available at

www.guyard-sa.fr