



Notice : *BOA SKIN F*

Index : 2

GUYARD SAS

22-24, rue Lucien Rouzet
Z.A. Villedieu sur Indre/Niherne
36250 NIHERNE FRANCE

Intermediate risks - PPE de category II

EN ISO 21420 :2020 EN 388 :2016+A1 :2018
EN 407 :2020 EN ISO 13997 :1999

FEATURES :

- Gloves made of polyethylene fiber, HPPE, stainless steel, and
- Nitrile reinforcement on the grip, tactile glove.
- Elastic wrist with a color indicating the size.
- Gauge 18, length from 22 to 27 cm.

AVAILABLE SIZES :

- Sizes 5 to 13.

ISO 21420 :2020 EN 388 :2016+A1 :2018 EN 407 :2020



4 X 4 3 F

X 1 X X X X

USAGE PRECAUTIONS :

- Wear the gloves on clean, dry hands. It is recommended to perform a preliminary test of the gloves, as actual usage conditions may differ from EU type testing.
- Before reusing, check that the gloves do not have defects, holes, tears, or abnormal wear.
- Shelf life: 5 years from the date of manufacture indicated on the glove.

SAFETY, COMFORT AND DEXTERITY :

- Dexterity level 5
- The glove does not contain substances at levels known or suspected to have adverse effects on the hygiene or health of the user under foreseeable conditions of use.

PACKAGING

- In case of unpacking, a copy of the instructions must be included with the smallest packaging.
- Bag of 10 pairs
- Carton of 100 pairs

MARKING :

- The CE marking on this glove indicates compliance with the essential health and safety requirements of the European Regulation 2016/425 related to personal protective equipment (PPE).

PERFORMANCES LEVELS :

EN 388 :2016+A1 :2018

- | | |
|------------------------------|-----|
| Abrasion : | 4/4 |
| Cut resistance : | X/5 |
| Tear resistance : | 4/4 |
| Puncture resistance : | 3/4 |
| Cut resistance (ISO 13997) : | F/F |

EN 407 :2020

- | | |
|----------------------------------|-----|
| Fire behavior | X/4 |
| Contact heat : | 1/4 |
| Convective heat : | X/4 |
| Radiant heat : | X/4 |
| Small splashes of molten metal : | X/4 |
| Large splashes of molten metal : | X/4 |

LIMITS OF PROTECTION

- Do not use for handling objects at temperatures above 100°C.
- Do not use for handling chemicals.

RECOMMENDED USES :

- Handling of dry or greasy sharp parts.
- Industry, mechanics.

CARE AND STORAGE

- No special maintenance is recommended. It is advised to store the products in a place away from light, cool, dry, and well-ventilated.

END OF LIFE

- The end-of-life disposal must be controlled and comply with European requirements for traceability and environmental protection.

EU type certificate issued according to module B of regulation (UE) 2016/425
The EU Declaration of Conformity is available at

ZVD n° :1493

www.guyard-sa.com