

1					2					3					4				
COUNT	DESCRIPTION OF REVISIONS				BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS				BY	CHKD	DATE				
△								△											
△								△											
△								△											

DETAIL OF MOUNTING GUIDE

PANEL CUTOUT
(PANEL THICKNESS 0.7 TO 2)

MAIN GUIDE

DIP LOCATION DIMENSION FROM CONNECTOR INTERFACE

NOTE: ① THE RECOMMENDED TIGHTEN TORQUE OF REF.NO.⑥: 1.5N·m.
ADHESIVE LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS
RECOMMENDED TO PREVENT REF.NO.⑥ FROM LOOSENING.

3	POLYAMIDE	(BLACK) UL94V-1	6	BRASS	NICKEL PLATED
2	STAINLESS STEEL		5	PHOSPHOR BRONZE	NICKEL PLATED
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	4	BERYLLIUM COPPER	OVERPLATING : GOLD 0.2μm min UNDERPLATING : NICKEL 2.0μm min
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	TSUZUKI 06.07.22	Y. Yamada 06.07.22	M. Gawa 06.07.22	M. Sato 06.07.22	

	DRAWING NO.	PART NO.
	EDC4-022725-73	HR10-7R-4SA(73)
SCALE 2 : 1	HRS HIROSE ELECTRIC CO., LTD.	CODE NO.
UNITS mm		CL110-0059-9-73

TO

R

1

2

3

4

FORM NO. 228