

## AIKIDO MID ESD

**S3S FO SR**

FTI 1182 BI1 03



### SPECIFICATIONS

Upper	highly breathable suede effect microfibre upper
Lining	BI-FRESH PLUS 3D lining with high breathability and top abrasion resistant
Toe-cap	aluminium BI-ALLOY
Nail protection	Zero Perforation fabric PS BI-SAFE metal-free
Sole	Bi-density PU with BI-SHANK arch support and resilient anti-shock insert
Insole	DAMPER PRO
Sizes	36/48
Fit	Mondopoint 11
Safety Norms	EN ISO 20345:2022
Weight (Size 42)	655g

### WORK ENVIRONMENTS

Construction / Automotive / Logistics / Agriculture / Craftmanship / Precious metal / Light Industry / Engineering / Mechatronics / Warehousing



### DESCRIPTION

AIKIDO MID ESD is a sporty safety shoe in S3S protection class with highly breathable and water-repellent microfibre upper

### TOE-CAP



### COMPONENTS

**DAMPER PRO:** New insole in open-cell PU with antibacterial fabric, shaped and anatomical, it is designed to increase comfort, shock absorption, especially in the heel area, improving the discharge of energy accumulated while walking and moving weights

### INSOLE


**BI-ALLOY:** New ultra-light and non-magnetic toe cap, made with approximately 56% recycled aluminum. The special production system makes it extremely reliable even in the most critical situations. The toe-protection band makes it very comfortable.

### STANDARD LABEL



### PLUS

**BI-BALANCED:** is the new TPU stabilisation system applied to the heel of the shoe, which reduces the risk of twisting, and therefore accidents, on all types of terrain, even the most bumpy and uneven

**Calzaturificio 5BI S.r.l.**  
 Via Trani, 94-100  
 76121 Barletta (BT)

**BI-FRESH PLUS:** Three-dimensional Polyester lining with high abrasion resistance and breathability


FTI 1182 BI1 03

42

bicap.it

**BI-SHANK:** Special resilient PU insert, which does not warp with use, and with a stabilizing anti-torsion system, which holds up and supports the foot, joints and the back. It also improves posture, offers optimal shock dissipation with a pleasantly comfortable effect, even for long periods

**S3S FO SR**


Year and month of manufacture

Lot / Batch Number

EN ISO 20345:2022



do not re-use

#VALORE!