

## **SOLISTRAND**

TE Internal #: 321878

Closed Ring Tongue Terminal, 4/0 AWG, 3/8 Stud, 9.53 mm / 9.91 mm [.39 in] Stud Diameter, Closed Barrel, Straight, Tin Plating,

Uninsulated

View on TE.com >



Terminals & Splices > Ring Terminals











Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 190000 - 231100 CMA

Stud Size: 3/8

# **Features**

## **Product Type Features**

Product Type Features	
Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	3/8
Sealable	No
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Number of Holes	2
Body Features	
Product Weight	55.108 g
Contact Features	
Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Tin
Contact Underplating Material	Copper
Mechanical Attachment	

Without

Wire Insulation Support



## **Dimensions**

Wire Size	190000 – 231100 CMA
Stud Diameter	9.53 mm, 9.91 mm[.39 in]
Tongue Thickness	.79 mm[.031 in]
Product Length	55.32 mm[2.178 in]
Barrel Inside Diameter	16.13 mm[.635 in]

# **Usage Conditions**

Inculation Option	Uninsulated
Insulation Option	Uninsulated

## Operation/Application

Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin

# **Industry Standards**

# **Packaging Features**

Packaging Quantity	50
Packaging Method	Loose Piece

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these




limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts











# Customers Also Bought























# **Documents**

# **Product Drawings**

TERMINAL, SOLIS R 4/0 3/8

English

## **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_321878\_U.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_321878\_U.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_321878\_U.3d\_stp.zip

English

3D PDF

English

**Customer View Model** 

ENG\_CVM\_321878\_H.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_321878\_H.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_321878\_H.2d\_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## **Instruction Sheets**

Instruction Sheet (U.S.)

English

# **Agency Approvals**

**UL Report** 

English

Closed Ring Tongue Terminal, 4/0 AWG, 3/8 Stud, 9.53 mm / 9.91 mm [.39 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Uninsulated



**UL Report** 

English