Product data sheet Characteristics

NHLF36000S15TW

Automatic Switch - PowerPacT multistandard - H-Frame - 150 A - 125 KA



Main

Range of product	PowerPact multistandard
Range	PowerPact
Product name	H-Frame
Device short name	H-Frame
Product or component type	Circuit breaker
Device application	Distribution

Complementary

Complementary	
Poles description	3P
Control type	Toggle
Mounting mode	Fixed
Mounting support	Flush Backplate DIN rail
[ln] rated current	150 A at 40 °C
[Ui] rated insulation voltage	750 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-2
[Ue] rated operational voltage	525 V AC 50/60 Hz conforming to IEC 60947-2
Breaking capacity code	HL
Suitability for isolation	Yes
Utilisation category	Category A
Mechanical durability	5000 cycles
Electrical durability	1000 cycles
Connection pitch	45 mm
Local signalling	ON/OFF indication
Contact position indicator	Yes
Trip unit rating	2250 A
Breaking capacity	Icu: 100 kA at 220/240 V - AC conforming to IEC 947-2 Icu: 65 kA at 380/415 V - AC conforming to IEC 947-2 Icu: 65 kA at 440/480 V - AC conforming to IEC 947-2 Icu: 25 kA at 500/525 V - AC conforming to IEC 947-2 100 KA at 240 V - AC conforming to UL 489 65 KA at 480 V - AC conforming to UL 489 25 kA at 600 V - AC conforming to UL 489
[lcs] rated service breaking capacity	lcs: 125 kA at 220/240 V - AC conforming to IEC 947-2 lcs: 100 kA at 380/415 V - AC conforming to IEC 947-2 lcs: 100 kA at 440/480 V - AC conforming to IEC 947-2 lcs: 50 kA at 500/525 V - AC conforming to IEC 947-2
Overvoltage category	II
Provision for padlocking	Non padlockable
Height	163 mm
Width	104 mm
Depth	86 mm

Standards	UL 489	
	IEC 60947-2	
	CSA C22.2 No 5	
	NEMA AB1	
	W-C-375B/GEN	
	NMX J-266	
Product certifications	CCC[RETURN]CE	
Net weight	2.2 kg	

Environment

IP degree of protection	IP40 conforming to IEC 60529	
IK degree of protection	IK07 conforming to IEC 62262	
Pollution degree	3 conforming to IEC 60947-1 3 conforming to IEC 60664-1	
Ambient air temperature for operation	40 °C	
Ambient air temperature for storage	-5085 °C	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	