# 4-1703639-1 ACTIVE

#### AMP | Heavy Duty Sealed Connector Series

TE Internal #: 4-1703639-1

Heavy Duty Sealed Connector Series, Housing for Female Terminals, Wire-to-Wire, 12 Position, .157 in [4 mm] Centerline,

Sealable, Black, Signal

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > Heavy Duty Sealed Connector Series Housings











Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: 1.6 mm [.063 in ]
Connector System: Wire-to-Wire

Number of Positions: 12

Centerline (Pitch): 4 mm [ .157 in ]

Nominal Voltage Architecture

All Heavy Duty Sealed Connector Series Housings (186)

## **Features**

#### **Product Type Features**

Troduct Type readures	
Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	12
Number of Rows	2
Electrical Characteristics	
Operating Voltage	60 VDC

12 V, 24 V, 42 V, 60 V



## **Body Features**

Cable Exit Angle	Other
Body Material	PBT GF
Primary Product Color	Black
Connector Code	04

#### **Contact Features**

Contact Size	1.5K
Mating Tab Width	1.6 mm[.063 in]
Contact Current Rating (Max)	20 A

#### Mechanical Attachment

Mounting Feature	Without
Terminal Position Assurance	Yes
Strain Relief	No
Mating Alignment Type	Keyed
Mating Alignment	With

## **Housing Features**

Centerline (Pitch)	4 mm[.157 in]
--------------------	---------------

# Dimensions

Product Width	25.7 mm[1.012 in]
Product Length	54.1 mm[2.13 in]
Product Height	31.25 mm[1.23 in]

# **Usage Conditions**

Operating Temperature (Max)	70 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C,
	110 °C, 120 °C, 125 °C, 130 °C, 140 °C[158 °
	F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F][266 °F][284 °F]
Operating Temperature Range	-40 - 140 °C[-40 - 284 °F]

# Operation/Application

Circuit Application	Signal	
Industry Standards		

# Degree of Protection IP67 UL Flammability Rating UL 94V-0

# **Packaging Features**



Packaging Quantity	300
Packaging Method	Box
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





TE Part # 964972-1 EINZELLEITERDICHTNG



TE Part # 2112302-1
PROTECTION CAP, FOR REC.HSG
GROUP D



TE Part # CAT-H3399-B128

Heavy Duty Sealed Connector Series

Backshells





# Also in the Series | Heavy Duty Sealed Connector Series



Automotive Connector Caps & Covers (23)



Automotive Housings(193)



Automotive Seals & Cavity Plugs(5)



Other Automotive Connector Accessories(22)

# Customers Also Bought









## **Documents**

**Product Drawings** 

12POS,AMP MCP1.5K,REC HSG,ASSY,CODD

English

#### **CAD Files**

Customer View Model ENG\_CVM\_CVM\_4-1703639-1\_J.2d\_dxf.zip



English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_4-1703639-1\_J.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_4-1703639-1\_J.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

**HDSCS Catalog** 

English

ICT Terminals and Connectors Catalogue

English

**CONNECTOR SELECTOR** 

English