

trip unit MicroLogic 2.0, ComPact NS630b to NS3200 fixed and drawout, basic protections

Local distributor code: 383429751 33504

EAN Code: 3303430335047

Main

Range	ComPacT	
Range of product	ComPacT NS630b1600 new generation	
Product or component type	Trip unit	
Trip unit name	MicroLogic 2.0	
Trip unit technology	Electronic	
Range compatibility	ComPacT NS630b1600	
Device application	Distribution	
Number of poles	4P 3P	
Protected poles description	4t 3t 3t + N/2	
Trip unit protection functions	Basic protection	
Protection type	for overload protection (long time) for instantaneous short-circuit protection	
Trip unit rating	630 A at 50 °C 800 A at 50 °C 1000 A at 50 °C 1250 A at 50 °C 1600 A at 50 °C 2000 A at 50 °C 2500 A at 50 °C 3200 A at 50 °C	
Network type	AC	
Network frequency	50/60 Hz	
Circuit breaker mounting mode	Fixed Drawout	

Complementary

Long-time pick-up adjustment type Ir (thermal protection)	Adjustable 9 settings
[Ir] long-time protection pick-up adjustment range	0.41 x ln
Long-time protection delay adjustment type tr	Adjustable 9 settings
[tr] long-time protection delay adjustment range	0.716.6 s at 7.2 x lr 0.524 s at 6 x lr 12.5600 s at 1.5 x lr
Thermal memory	20 mn
Instantaneous protection pick-up adjustment type li	Adjustable 9 settings

4 Jul 2025 Life Is On Schneider

[li] instantaneous protection pick- up adjustment range	1.510 x lr	
Earth-leakage protection	Without	
Zone selective interlocking ZSI	Without	
Local signalling	3 LEDs (red) for electrical fault 1 LED (red) for internal error	

Environment

Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-5085 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.500 cm
Package 1 Width	13.500 cm
Package 1 Length	38.000 cm
Package 1 Weight	306.000 g
Unit Type of Package 2	P12
Number of Units in Package 2	32
Package 2 Height	45.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	28.192 kg

Logistical informations

Country of origin

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	19
Environmental Disclosure	Product Environmental Profile

Use Better

Recycled metal content at CR level	0
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	6ac3934d-9e20-40a3-adef-08cec90e29e2
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins