

FLOYD S3 LOW




STANDARD EN ISO 20345 : 2011



LEMAITRE

Safety since 1974

CARBON
by LEMAITRE







Carbon fiber toe-cap
Cutting-edge technology from
the aeronautical industry



Sizes 35 to 49 Reference code: FLOYD30NR

Product Highlights

-  **Carbon toe-cap by Lemaitre** : ergonomic build, lightness, similar resistance to steel, athermic and non-magnetic
- Memory Foam insole by Lemaitre**: anti-bacterial memory structure, odor neutralizer, MSDs prevention
-  **1.7-1.8 mm thick leather** and retro-reflective side marker, enhanced visibility
- Bellows Tongue**: to limit intrusion of dust and stones
- Reinforced abrasion-resistant cap, increased resistance
-  **Protective toe-cap**: Carbon by Lemaitre
-  **Puncture resistant midsole**: high tenacity fabric "0" penetration



Anti-static sole CARBON PU2D

- Developed outsole for industrial and urban floors**
- Large bearing surface**: optimal stability
- Shock absorption**: preservation of the back and joints
- Conformal to bent positions**: knee notches and crouching
- Sculpted studs**: reinforced grip

USAGE

- Finishing works, light industry, logistics, services, handling



lemaitre-secureite.com

An exacting attitude to quality is our culture, safety our priority



FLOYD S3 LOW



STANDARD EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material** : water-repellent microfiber with an abrasion-resistant cap in "groove"
- **Bellows tongue**: abrasion-resistant textile
- **Collar** : abrasion-resistant textile
- **Lining**: 3D microporous fabric

Characteristics of the sole

- **Designation** : CARBON PU2D
- **Material** : polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient** :
forward flat slip: 0,34 (standard \geq 0,32)
forward heel slip: 0,31 (standard \geq 0,28)
- **SRB Adhesion coefficient** :
forward flat slip: 0,22 (standard \geq 0,18)
forward heel slip: 0,20 (standard \geq 0,13)

VARIANT



Felix S3 SRC
FELIS30NR

Practical Information

Weight of one shoe size 42 : 540 g

CERTIFICATION N° 0075/007/161/09/19/2718 EXT 07/03/20

Packaging

sizes 35 to 42

shoebox 315 x 220 x 123 mm

carton 635 x 445 x 315 mm

10 shoeboxes per carton

sizes 43 to 49

shoebox 355 x 220 x 130 mm

carton 660 x 450 x 360 mm

10 shoeboxes per carton

Gencods

35	3237154284353	43	3237154284438
36	3237154284360	44	3237154284445
37	3237154284377	45	3237154284452
38	3237154284384	46	3237154284469
39	3237154284391	47	3237154284476
40	3237154284407	48	3237154284483
41	3237154284414	49	3237154284490
42	3237154284421		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP



S1



S1P



S2



S3



200 J toe-cap: protection of the forefoot against impact and crushing



Anti-perforation insert 1100 N: foot protection against perforation



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



SRC = SRA + SRB

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com



LEMAITRE
Safety since 1974

DON_LS 04 TDS 0018
Update : 10/03/20

Member of
SYNAMAP

