



EN ISO 20345:2011


 POLAR
EMPIRE
88169-00L
S3 HRO HI WR CI SRC
Size: 38-48
Weight: 850 gr.

Fit: 11

Working Environment:
 Building, Farming and Gardening,
 Mountains, Cold places


FEATURES

UPPER

 Full Grain-Anilina Leather-Hydro
 1,8-2,0 mm
 Full Grain leather Hydro
 Reflex insert

LINING

 3D Air circulation 320 gr.
 GenuineWool Polar

ANTISLIP LINING

DUALMICRO

INSOLE

Dual insulation

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

SOLE

PU-RUBBER VIBRAM-HRO-SRC

 Sole resistant to 300°C by contact.
 With scaff cap and compound
 designed with VIBRAM for stability
 and grip performance. Outsole
 designed to strike the ground
 better and to improve self-
 cleaning. With anti-wear scaff cap.

TECHNOLOGIES

Removable Insole


 Insole perfect for winter use and for
 footwear with protection against cold
 "CI". It consists of a highly resistant
 and absorbing felt piece that keeps
 the foot dry and warm and of an
 aluminised film to isolate the foot
 from the ground.


Protection elements


 RESISTANT
 TO 3.0 mm.
 NAILS

 fibercap **sxt**

 Composite toecap with fiberglass.
 Resistant to over 200J. Non metal
 perforation resistant insert to over
 1100 N with a 3.0 mm truncated cone
 nail. Protection over the entire sole of
 the foot. Flexible and comfortable


Lateral stability

 dynamic **HC** control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability


STABIL•ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features



Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.


Other


 The HDry membrane is hydrophilic
 with high perspiration capacity. It
 guarantees high performance and
 durability, facilitating the
 maintenance of ideal conditions and
 comfort for the user.


SRC (SRA+SRB)


 SOLE 88
 PU - RUBBER

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.34
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.19
		0.15

EN ISO 20344:2011