

Complete body/contact assembly, Harmony XB4, single contact block with body/fixing collar 1NC spring clamp terminal

Local distributor code: 409065484 ZB4BZ1026P

EAN Code: 3606480502408

Main

Range of product	Harmony XB4	
Product or component type	Complete body/contact assembly	
Device short name	ZB4	
Fixing collar material	Zamak	
Sale per indivisible quantity	1	
Head type	Standard	
Contacts type and composition	1 NC	
Contact operation	Slow-break	
Contact block type	Single	
Device composition	Contact block Fixing collar	
Connections - terminals	Screw clamp terminals, \leq 2 x 1.5 mm ² with cable end conforming to IEC 60947-1 Screw clamp terminals, \geq 1 x 0.22 mm ² without cable end conforming to IEC 60947-1	

Complementary

CAD overall width	30 mm	
CAD overall height	47 mm	
CAD overall depth	37 mm	
Terminals description ISO n°1	(11-12)NC	
Net weight	0.064 kg	
Contacts usage	Standard contacts	
Positive opening	With conforming to IEC 60947-5-1 appendix K	
Operating travel	1.5 mm (NC changing electrical state) 2.6 mm (NO changing electrical state) 4.3 mm (total travel)	
Operating torque	0.05 N.m NO changing electrical state	
Mechanical durability	5000000 cycles	
Contacts material	Gold flashed (Ag/Ni/Au) contacts	
Short-circuit protection	4 A cartridge fuse type gG conforming to IEC 60947-5-1	
[Ith] conventional free air thermal current	10 A conforming to IEC 60947-5-1	
[Ui] rated insulation voltage	250 V (pollution degree 3) conforming to IEC 60947-1	
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1	

[le] rated operational current	3 A at 240 V, AC-15, A300 conforming to IEC 60947-5-1 6 A at 120 V, AC-15, A300 conforming to IEC 60947-5-1 0.1 A at 250 V, DC-13, R300 conforming to IEC 60947-5-1 0.22 A at 125 V, DC-13, R300 conforming to IEC 60947-5-1
Electrical durability	1000000 cycles, AC-15, 1 A at 230 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 1.5 A at 120 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 3 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.15 A at 110 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.4 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
Electrical reliability	Λ < 10exp(-6) at 5 V, 1 mA in clean environment conforming to IEC 60947-5-4 Λ < 10exp(-8) at 17 V, 5 mA in clean environment conforming to IEC 60947-5-4

Environment

Protective treatment	тн	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-2570 °C	
IP degree of protection	IP20 conforming to IEC 60529	
Standards	IEC 60947-5-5 CSA C22.2 No 14 IEC 60947-5-1 UL 508 JIS C8201-5-1 IEC 60947-5-4 IEC 60947-1 JIS C8201-1	
Product certifications	BV UL CSA DNV LROS (Lloyds register of shipping)	
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6	
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.1 cm
Package 1 Width	1.2 cm
Package 1 Length	3.5 cm
Package 1 Weight	53.0 g

Logistical informations

Country of origin

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins