

1552324

https://www.phoenixcontact.com/gb/products/1552324

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 5-position, Pin, straight, M12-SPEEDCON, coding: B, Rear mounting, Pg9, Solder pins, this item is undergoing a smooth changeover, lead-free alternative in accordance with RoHS II without exception 6c (Pb < 0.1%) possible on request in advance

Your advantages

- Easy PCB assembly: one-piece connectors for wave soldering
- · All standard pin assignments and codings for signal, data, and power transmission with a uniform design-in design
- · SPEEDCON fast locking system reduces cabling times

Commercial data

Item number	1552324
Packing unit	20 pc
Minimum order quantity	20 pc
Sales key	ABQEGL
Product key	ABQEGL
Catalog page	Page 246 (C-2-2013)
GTIN	4046356162173
Weight per piece (including packing)	13.79 g
Weight per piece (excluding packing)	12.536 g
Customs tariff number	85366990
Country of origin	DE



1552324

https://www.phoenixcontact.com/gb/products/1552324

Technical data

Notes

Notes on operation	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Order information:	Lock nut is included in the scope of delivery

Mounting

Mounting type	Rear mounting Pg9 With flat nut
Assembly note	With flat nut

Product properties

Product type	Circular connectors (device side)
Number of positions	5
Shielded	no
Coding	В
Thread type	M12
Insulation characteristics	

П

3

Dimensions

Length of the solder pin	12 mm
	12 mm

Material specifications

Overvoltage category

Degree of pollution

Flammability rating according to UL 94	V0
Seal material	NBR
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 6.6
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Rated surge voltage	1.5 kV
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U _N	60 V
Nominal current I _N	4 A



1552324

https://www.phoenixcontact.com/gb/products/1552324

Connection data

Conductor connection

Connection method	Solder pins
Contact connection type	Pin
Tightening torque	2 Nm 3 Nm (Installation-side)

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	> 100

Connector

Connection 1

Head design	Pin
Head cable outlet	straight
Head thread type	M12
Head locking type	SPEEDCON
Coding	В

Cable/line

Ambient temperature (operation)	-40 °C 85 °C (cable, fixed installation)
	-25 °C 85 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67 (When plugged in)
	IP65 (When plugged in)
	IP65/IP67
Ambient temperature (operation)	-25 °C 85 °C (Plug / socket)
	-40 °C 85 °C (without mechanical actuation)
	-25 °C 85 °C (Cable, flexible installation)
	-40 °C 85 °C (cable, fixed installation)

Standards and regulations

Standard designation	M12 circular connector
Standards/specifications	according to IEC 61076-2-101




1552324

https://www.phoenixcontact.com/gb/products/1552324

Drawings

Schematic diagram



Pin assignment M12 male connector, 5-pos., B-coded, male side



1552324

https://www.phoenixcontact.com/gb/products/1552324

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/1552324

c 911 us	cULus Recognized Approval ID: E221474-20140616				
	Nominal voltage U_N	Nominal current I _N	Cross section AWG	Cross section mm ²	
	60 V	4 A	-	-	

UL Recognized Approval ID: E118976-20100522					
		Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
		60 V	4 A	22	-



1552324

https://www.phoenixcontact.com/gb/products/1552324

Classifications

_	\sim	Δ	C	C
_		ч	. つ	. ``

	ECLASS-13.0	27440110
E	ГІМ	
	ETIM 9.0	EC003569
UI	NSPSC	
	UNSPSC 21.0	39121400



1552324

https://www.phoenixcontact.com/gb/products/1552324

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	d058a203-ead9-4a83-b365-ef954e58306e

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT Ltd Halesfield 13, Telford Shropshire, TF7 4PG 01952 681700 info@phoenixcontact.co.uk