

Product data sheet

Specifications



Repacked, load-shedder, Acti9 DSE1, 1 C, white

A9C15907W



This repacked option saves 1.421 over the standard condition

Main

range of product	Acti9
Product or component type	Load-shedder
Device short name	DSE1
Number of channels	1
Control and monitoring type	Cascade
Poles description	1P

Complementary

Setting	3.5...32 A +/- 1 %
Power consumption in VA	3.5 VA
[Ue] rated operational voltage	230 V AC +/- 10 % at 50/60 Hz
Rated current	32 A for priority circuit > 16 A relaying by contactor for non-priority circuit < 16 A for non-priority circuit
Local signalling	Load-shedding indication: 1 LED (red) Load-shedding indication: buzzer
Display type	LCD screen
Maximum value measured	9.999 kW
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	4
Connections - terminals	Screw terminal6 mm²
IP degree of protection	IP40 IP20
Height	87 mm
Width	36 mm
Depth	60 mm
Product weight	0.13 kg
Colour	White (RAL 9003)

Environment

Ambient air temperature for operation	-5...50 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 cm
Package 1 Width	8.400 cm
Package 1 Length	12.800 cm
Package 1 Weight	166.000 g
Unit Type of Package 2	S01
Number of Units in Package 2	12
Package 2 Height	15.000 cm
Package 2 Width	15.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	2.180 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Lower carbon footprint

1 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

SCIP Number

429095ee-388a-4184-bea4-16f87e374975

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins