



Notice : BOA FOAM FULL F

Index : 2

GUYARD SAS

22-24, rue Lucien Rouzet
Z.A. Villedieu sur Indre/Niherne
36250 NIERNE FRANCE

Intermediate risks - Category II PPE

EN ISO 21420 :2020 EN 388 :2016+A1 :2018
EN 407 : 2020 EN ISO 13997 :1999

FEATURES :

- High-density polyethylene fibre glove, stainless steel wire, elastane-thane, fully coated with nitrile foam
- Nitrile gripper reinforcement. Gauge 13.
- Tactile glove.
- Elasticated handle with coloured overlock to indicate size.

AVAILABLE SIZE :

- Sizes 6 to 12

PRECAUTIONS FOR USE :

- Wear gloves on dry, clean hands. It is recommended that gloves be tested before use. Actual conditions of use may differ from EU type testing.
- Before re-use, check gloves for defects, holes, tears or abnormal wear.
- Shelf life: 5 years from the date of manufacture indicated on the glove.

SAFETY COMFORT AND DEXTERITY :

- Dexterity level 5
- The glove does not contain substances at levels known or suspected to have adverse effects on the hygiene or health of the user under the foreseeable conditions of use.

PACKAGING

- In the event of unpacking, a copy of the package leaflet must be enclosed with the smallest pack.
- Bag of 10 pairs
- Box of 100 pairs.

MARKING :

- The CE mark affixed to this glove signifies compliance with the essential health and safety requirements of European Regulation 2016/425 on personal protective equipment (PPE).

EN 388 :2016+A1 :2018



4 X 4 3 F

EN 407 :2004



X 1 X X X X

PERFORMANCE LEVELS :

EN 388 :2016

- | | |
|--|-----|
| • Abrasion : | 4/4 |
| • Blade cut : | X/5 |
| • Tear : | 4/4 |
| • Puncture : | 3/4 |
| • Cutting by sharp objects (ISO 13997) : | F/F |

EN 407 :2004

- | | |
|------------------------------------|-----|
| • Fire behaviour | X/4 |
| • Contact heat : | 1/4 |
| • Convective heat : | X/4 |
| • Radiant heat: | X/4 |
| • Small splashes of liquid metal : | X/4 |
| • Large splashes of liquid metal: | X/4 |

PROTECTION LIMITS

- Do not use for handling objects at temperatures above 100°C.
- Do not use for handling chemicals or liquids.

RECOMMENDED USES :

- Handling dry or greasy cutting
- Industry and mechanical engineering.

MAINTENANCE AND STORAGE

- No special maintenance is recommended. Products should be stored in a cool, dry, well-ventilated place away from direct light.

END OF LIFE

- End-of-life destruction must be controlled and comply with European traceability and environmental requirements.

EU Type Certificate issued in accordance with Module B Regulation (EU) 2016/425
The EU Declaration of Conformity is available on

ZVD n° :1493
www.guyard-sa.com