
Professional CEE cable reel KD 3200 C1 IP 44 30 m H07RN-F 5G2.5

For construction site use in accordance with DGUV 203-006 (formerly BGI 608) and permanent outdoor use IP 44.









MADE IN GERMANY | 5 YEARS MANUFACTURER GUARANTEE | DGUV-I 203-006 K2 | VDE 0100 Teil 704 | SPECIAL ROBUST | IP 44

Product number	9222300110
EAN	4007123687602

DESCRIPTION

- Professional drum with all-round roll-over protection.
- Stable on all four sides - perfect cable routing on all four sides.
- Large, sturdy folding twist handle for effortless winding and unwinding of the cable.
- Robust carrying handles and plug garage on all four sides.
- The Rubbabren housing and drum material made of a plastic-rubber mix is extremely shock and impact resistant. For continuous use under the toughest conditions.
- Reel body cold impact resistant down to -25 °C.
- The RN cable is very robust, oil-resistant and particularly suitable for professional use.
- RN cable is approved for harsh building conditions in accordance with VDE 0100 Part 704.
- CEE plug 400 V/16 A, 1 CEE socket 400 V/16 A, 2 splash-proof protective contact sockets 230 V.
- Sockets with earthing contact distributed on separate phases.
- With 3-pole safety cut-out and overheating protection.
- Category 2 equipment (K2 DGUV 203-005): For use in harsh operating conditions with high mechanical, physical and chemical influences.

Professional CEE cable reel KD 3200 C1 IP 44 30 m H07RN-F 5G2.5

For construction site use in accordance with DGUV 203-006 (formerly BGI 608) and permanent outdoor use IP 44.



Product number	9222300110
EAN	4007123687602

TECHNICAL DATA

Cable quality	Rubber-Neoprene	**Plug system socket**	Type F (Protective contact)
Cable length	30 m	**Plug system plug**	CEE 16 A 3P+N+E (5p) 400 V
Cable designation	H07RN-F 5G2,5	**Max. current carrying capacity**	16 A
Cable colour	black	**Nominal input voltage**	230 V/400 V
Reel diameter	320 mm	**Degree of protection (IP)**	IP44
Plug system CEE socket	CEE 1x 16 A 3P+N+E (5p) 400 V		

PACKAGING, DIMENSIONS AND WEIGHTS

UP	1	**Weight of product (including packaging)**	11.95 kg
Weight of product (without packaging)	11.94 kg	**Dimension LxWxH (incl. packing)**	26 cm x 38.7 cm x 40 cm
Dimension LxWxH (without packing)	26 cm x 37 cm x 37 cm		

SCOPE OF DELIVERY

Professional CEE-Kabeltrommel KD 3200 C1