

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021

Revision date 13-Dec-2022 Revision Number 1.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK BORN2BOND PREBONDING CLEANER

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

None known

Recommended use Cleaning agent

1.3. Details of the supplier of the safety data sheet

Company Name

Uses advised against

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity — single exposure	Category 3 - (H336)
Category 3 Narcotic effects	
Chronic aquatic toxicity	Category 2 - (H411)
Aerosols	Category 1 - (H222, H229)

2.2. Label elements

Contains Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane, Isopropyl alcohol

United Kingdom - BE Page 1 / 14

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021 Revision Number 1.02

Revision date 13-Dec-2022



Signal word Danger

Hazard statements

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

Precautionary Statements - EU (§28, 1272/2008)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211 - Do not spray on an open flame or other ignition source

P251 - Do not pierce or burn, even after use

P261 - Avoid breathing vapours/spray

P280 - Wear protective gloves and eye/face protection

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

P391 - Collect spillage

P273 - Avoid release to the environment

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture. Toxic to aquatic life. In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	RR-100219-3	>25 - <40	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411)	-	01-2119475515- 33-xxxx

United Kingdom - BE Page 2 / 14

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021 Revision Number 1.02

Revision date 13-Dec-2022

				Flam. Liq. 2 (H225)		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane	921-024-6	RR-100221-7	>25 - <40	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225)	-	01-2119475514- 35-XXXX
Isopropyl alcohol	(603-117-00- 0) 200-661-7	67-63-0	20 - 25	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	01-2119457558- 25-XXXX
Carbon dioxide	204-696-9	124-38-9	1 - <5	Press. Gas (H280)	-	[4]

NOTE [4] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex IV of REACH

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Show this safety

data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical

attention immediately if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical

attention if irritation develops and persists.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. Call a doctor.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin,

eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

SymptomsMay cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

United Kingdom - BE Page 3 / 14

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021 Revision Number 1.02

vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray.

Unsuitable extinguishing media Full water jet. DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE

STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only

Revision date 13-Dec-2022

by specialists. Containers may explode when heated.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO2).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take

precautionary measures against static discharges. Avoid breathing

dust/fume/gas/mist/vapours/spray.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without

risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

United Kingdom - BE Page 4 / 14

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

Revision date 13-Dec-2022

Revision Number 1.02

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Keep/store only in original container. Store in a dry place. Store in a closed container.

Recommended storage temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s) Cleaning agent.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Observe technical data sheet. Other information

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Isopropyl alcohol	-	TWA: 400 ppm
67-63-0		TWA: 999 mg/m ³
		STEL: 500 ppm
		STEL: 1250 mg/m ³
Carbon dioxide	TWA: 5000 ppm	TWA: 5000 ppm
124-38-9	TWA: 9000 mg/m ³	TWA: 9150 mg/m ³
		STEL: 15000 ppm

United Kingdom - BE Page 5/14

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021 Revision Number 1.02

Revision date 13-Dec-2022

Chemical name	European Union	Ireland	United Kingdom
Hydrocarbons, C6-C7, n-alkanes,	DNEL (Ind/Prof)	-	-
isoalkanes, cyclic, <5% n-hexane	773 mg/Kg bw/day (dermal)		
RR-100221-7	2035 mg/m ³ /8h (inhalation)		
Isopropyl alcohol	-	40 mg/L (urine - Acetone end of	-
67-63-0		shift at end of workweek)	

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
Hydrocarbons, C7, n-alkanes, isoa	alkanes, cyclics (RR-100219-	3)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term Systemic health effects	Inhalation	2085 mg/m ³			
worker Long term Systemic health effects	Dermal	300 mg/kg bw/d			

Туре	Exposure route	Derived No Effect Level	Safety factor
Long term Systemic health effects worker DNEL	Inhalation	(DNEL) 2035 mg/m³	
Long term Systemic health effects worker DNEL	Dermal	773 mg/kg bw/d	

Isopropyl alcohol (67-63-0)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker	Inhalation	,			
Long term	Illiaalion	500 mg/m ³			
Systemic health effects					
worker	Dermal	888 mg/kg bw/d			
Long term					
Systemic health effects					

Derived No Effect Level (DNEL)						
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Consumer Long term Systemic health effects	Inhalation	447 mg/m³				
Consumer Long term Systemic health effects	Dermal	149 mg/kg bw/d				
Consumer Long term Systemic health effects	Oral	149 mg/kg bw/d				

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane (RR-100221-7)					
Type	Exposure route	Derived No Effect Level	Safety factor		

United Kingdom - BE Page 6 / 14

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021

•

Revision date 13-Dec-2022

Revision Number 1.02

			
		(DNEL)	
Consumer	Dermal	699 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Inhalation	608 mg/m³	
Long term			
Systemic health effects			
Consumer	Oral	699 mg/kg bw/d	
Long term			
Systemic health effects			

Isopropyl alcohol (67-63-0)	sopropyl alcohol (67-63-0)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	89 mg/m³			
Consumer Long term Systemic health effects	Dermal	319 mg/kg bw/d			
Consumer Long term Systemic health effects	Oral	26 mg/kg bw/d			

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Isopropyl alcohol (67-63-0)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	140.9 mg/l
Marine water	140.9 mg/l
Sewage treatment plant	2251 mg/l
Freshwater sediment	552 mg/kg dry weight
Marine sediment	552 mg/kg dry weight
Soil	28 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Glove thickness > 0.7mm. Butyl rubber. Nitrile rubber. The

breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform

to standard EN 374

Skin and body protection Wear appropriate personal protective clothing to prevent skin contact.

Respiratory protection Ensure adequate respiratory protection during spray applications. In case of insufficient

ventilation, wear suitable respiratory equipment.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming

to EN 140 with Type A filter or better.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

United Kingdom - BE Page 7 / 14

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021 Revision Number 1.02

Revision date 13-Dec-2022

9.1. Information on basic physical and chemical properties

Physical state Aerosol Aerosol **Appearance** Colour Colourless Odour Solvent.

Odour threshold No information available

Values Remarks • Method **Property**

Melting point / freezing point Not applicable . °C None known

Initial boiling point and boiling Not applicable, Aerosol . Not applicable, Aerosol

range

Flammability No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Flash point Not applicable, Aerosol . Not applicable, Aerosol

Autoignition temperature 425 °C None known

Decomposition temperature None known

No data available

Not applicable. Insoluble in water.

pH (as aqueous solution) No data available None known Kinematic viscosity No data available None known

Dvnamic viscosity No data available

Water solubility Miscible in water. None known Solubility(ies) No data available None known Partition coefficient No data available None known Vapour pressure No data available None known Relative density 0.728 None known

No data available **Bulk Density Liquid Density** 0.72 - 0.73 g/cm³

Relative vapour density No data available None known

Particle characteristics

Particle Size No information available **Particle Size Distribution** No information available

9.2. Other information

Solid content (%) No information available

approx 694.5 g/L **VOC** content

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available. Reactivity

10.2. Chemical stability

Stable under normal conditions. Stability

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge

United Kingdom - BE Page 8/14

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021 Revision Number 1.02

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of

ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Incompatible materialsStrong acids. Strong bases. Strong oxidising agents. Incompatible with oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

Revision date 13-Dec-2022

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Specific test data for the substance or mixture is not available. May cause irritation

of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation.

(based on components).

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. May cause redness and tearing of the eyes. Inhalation of high vapour

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Acute toxicity

Numerical measures of toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C7, n-alkanes,	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat,
isoalkanes, cyclics			vapour)
·			(OECD 403)
Hydrocarbons, C6-C7,	LD50 >5840 mg/kg (Rattus)	LD50 >2800-3100 mg/kg	LD50 (4h) >25200 mg/m ³
n-alkanes, isoalkanes, cyclic,		(Rattus)	LD50 (4h) >20 mg/l (rattus) v
<5% n-hexane			

United Kingdom - BE Page 9 / 14

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021

·

Revision date 13-Dec-2022

Revision Number 1.02

Isopropyl alcohol	>5000 mg/Kg	= 4059 mg/kg (Oryctolagus	=72600 mg/m³ (Rattus) 4 h
		cuniculus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Isopropyl alcohol (67-63-0)

Method	Species	Exposure route	Effective dose	Exposure time	Results	
OECD Test No. 405:	Rabbit	eye			Irritant	
Acute Eye						
Irritation/Corrosion						

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Isopropyl alcohol (67-63-0)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig		No sensitisation responses
Sensitisation			were observed

Germ cell mutagenicity Based on av

Based on available data, the classification criteria are not met.

Component Information Isopropyl alcohol (67-63-0)

Method	Species	Results
OECD Test No. 476: In vitro Mammalian Cell	Hamster, in vitro	Not mutagenic
Gene Mutation Test		

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicityBased on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

United Kingdom - BE Page 10 / 14

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021

·

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Revision date 13-Dec-2022

Revision Number 1.02

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Hydrocarbons, C7,	ErL50 (72h) =	LL50 (96h)	-	EL50 (48h) =		
n-alkanes, isoalkanes,	10-30 mg/L	>13.4 mg/L		3.0 mg/L		
cyclics	(Pseudokirchner	(Oncorhynchus		(Daphnia		
RR-100219-3	iella subcapitata)	mykiss)		magna)		
		OECD 203				
Hydrocarbons, C6-C7,	EL50 (72h)= 26	LL50 (96h) =12	-	EL50 (48h)		
n-alkanes, isoalkanes,	mg/L	mg/L		=3mg/L		
cyclic, <5% n-hexane	(Pseudokirchner	(Oncorhynchus		(Daphnia		
RR-100221-7	iella subcapitata)	mykiss) OECD		magna) OECD		
	OECD 201	203		202		
Isopropyl alcohol	EC50 72 h >	LC50 96 h >	-	EC50:		
67-63-0	1000 mg/L	1400000 ?g/L		=13299mg/L		
	(Desmodesmus	(Lepomis		(48h, Daphnia		
	subspicatus)	macrochirus)		magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	98%	Readily biodegradable
Biodegradability: Manometric	-		
Respirometry Test (TG 301 F)			

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane (RR-100221-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	98%	Readily biodegradable
Biodegradability: Manometric			-
Respirometry Test (TG 301 F)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5%	4
n-hexane	
Isopropyl alcohol	0.05

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	The substance is not PBT / vPvB
Isopropyl alcohol	The substance is not PBT / vPvB PBT assessment does
	not apply

United Kingdom - BE Page 11 / 14

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021 Revision Number 1.02

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable. Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with

Revision date 13-Dec-2022

environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or

weld containers.

European Waste Catalogue 16 05 04* gases in pressure containers (including halons) containing dangerous

substances

15 01 04 metallic packaging

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number
14.2 Proper Shipping Name
14.3 Transport hazard class(es)
Labels
UN1950
Aerosols
2
2.2

14.4 Packing group Not regulated

Description UN1950, Aerosols, 2, (E), Environmentally Hazardous

14.5 Environmental hazards Yes

14.6 Special Provisions 327, 625, 344, 190

Classification code 5A Tunnel restriction code (E) Limited quantity (LQ) 1 L

IMDG

14.1 UN number or ID numberUN195014.2 Proper Shipping NameAerosols14.3 Transport hazard class(es)2.2

14.4 Packing group Not regulated

Description UN1950, Aerosols (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5%

n-hexane), 2.2, Marine Pollutant

14.5 Marine pollutant

14.6 Special Provisions 63,190, 277, 327, 344, 381, 959

Limited Quantity (LQ) See SP277
EmS-No F-D, S-U

14.7 Maritime transport in bulk Not applicable

according to IMO instruments

Air transport (ICAO-TI / IATA-DGR)

United Kingdom - BE Page 12/14

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021 Revision Number 1.02

Revision date 13-Dec-2022

4.4. LIN number of ID number LIN4050

14.1 UN number or ID number UN1950

14.2 Proper Shipping Name Aerosols, non-flammable

14.3 Transport hazard class(es) 2.2

14.4 Packing group Not regulated

Description UN1950, Aerosols, non-flammable, 2.2

14.5 Environmental hazards Yes

14.6 Special Provisions A145, A167, A98, A802

Limited quantity (LQ) 30 kg G ERG Code 2L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

P3b - FLAMMABLE AEROSOLS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

Regulation (EC) No. 648/2004 (Detergents regulation)

Labelling for contents according to regulation (EC) No. 648/2004

aliphatic hydrocarbons	>30%

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

United Kingdom - BE Page 13/14

BOSTIK BORN2BOND PREBONDING CLEANER

Supercedes Date: 01-Jul-2021 Revision Number 1.02

Revision date 13-Dec-2022

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour

H280 - Contains gas under pressure; may explode if heated

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H411 - Toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 13-Dec-2022

Indication of changes

Revision note SDS sections updated: 2, 3, 9, 11, 15, 16.

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 14/14